

Declaration of performance: No. 0014-CPR-2017/03/30

- 1) Unique identification code of the product-type *CALIBRO NHL*
- 2) Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer *Rendering and plastering mortar meets the requirements of UNI EN 998-1:2004 - Ready to use mortar designed specifically for plastering and for restoring damp walls (Type R)*
- 3) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5) *VOLTECO S.p.A. - Via delle Industrie, 47 - Ponzano Veneto (Italy) www.volteco.com*
- 4) System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in annex V *System 4*
- 5) In case of the declaration of performance concerning a construction product covered by a harmonised standard *Harmonised standard: UNI EN 998-1:2004*

6) Declared performance:

Essential characteristics	Performance
Reaction to fire	Class A1
Apparent bulk density	1.1÷1.2 kg/l
Compression strength	Class CSII
Adhesive bond	≥ 0.1 N/mm ² (FP A-type breaking)
Capillary absorption	≥ 0.3 kg/m ² (after 24 h)
Vapour permeability coefficient (μ)	≤ 15
Thermal conductivity (tabulated value)	0.40 W/mK
Air content	> 28%
Mixture bulk density	1.25÷1.35 kg/l
Hazardous substances	See SDS

7) The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacturer by **Marco Ruzzier** Laboratory Manager

(name and function)



Ponzano Veneto, 2017/03/30 -----

Rev. 1.0 2017/03/30