


Construction joint with AMPHIBIA 3000 GRIP under the slab and PLASTIVO on the foundation walls

Field	Underground waterproofing
Type of work	Reinforced concrete
Boundary conditions	Aquifer
Building construction	New
Excavation type	Free
Type of material(s)	HYDRO-REACTIVE SYSTEM
Sequence of installation	Before pouring concrete
Level of risk	High
Type of protection	Waterproofing barrier



1. Lean concrete blinding
2. Concrete protective screed (optional)
3. WT 102
4. Fillet with SPIDY 15
5. BI MASTIC or AKTI-VO 201
6. Separating protective element
7. Well compacted soil without voids
8. AMPHIBIA 3000 GRIP
9. RC raft foundation suitable to withstand hydraulic pressures and exempt from defects
10. RC wall suitable to withstand hydraulic pressures and exempt from defects
11. PLASTIVO
12. AMPHIBIA PRESSURE CORNER 90°
13. Rigid insulation panel or non-woven textile (min 250 g/m²)



PLEASE NOTE: Do not make Amphibia overlaps around the construction joint areas.

PLEASE NOTE: The waterproofing systems must be installed continuously all along the whole structure subjected to intervention and up till the ground level, keeping the continuity between all waterproofed surfaces, horizontal and vertical; any kind of joint, penetration and every possible crack must be sealed with suitable VOLTECO systems, applied in continuity with one another (see VOLTECO technical data sheets), in order to avoid any chance of seepage.

The structures must be suitable to withstand hydraulic pressures and every kind of load that they will undergo.

This proposed scheme (out of scale and released only for example purposes) and its implementation must be assessed and approved by the Designer and the Construction Supervisor in relation to the specific issues of the project and the building site. More information about the application, performances and technical data of the technologies that we have here described must be obtained from the product datasheets (also freely downloadable from the website www.volteco.it); those datasheets are considered part of this document.