



PROCLEAN

PRODUCT DESCRIPTION

PROCLEAN is a water-dispersed additive-based treatment with a disinfectant function, capable of neutralizing and protecting outdoor and indoor surfaces contaminated with mould, fungi and algae.



PRODUCT APPLICATION

Preparation of mineral or synthetic surfaces before applying CP0, CP1, PAINT AIR and PAINT PROTECTION, X-LIME and FIBROeRASO or levelling products and paints in general, to both prevent and remove deterioration caused by mould and algae.

Particularly suitable for:

- North-facing facades
- Outdoor or indoor wall surfaces with cement-based or lime plaster, lightweight plaster, both new and old
- Surfaces with synthetic finishes, quartz coatings or plastic paints
- Surfaces damaged by condensation, such as bathrooms, kitchens, cellars and under stairs
- Screeds or flooring affected by fungi, before waterproofing
- Concrete surfaces

ADVANTAGES

- It disinfects contaminated surfaces
- It does not require dilution with water
- Not film-forming
- Can be applied in closed and poorly ventilated environments as it is solvent-free
- It does not require washing after treatment

PREPARATION AND APPLICATION **Preparing the surfaces**

High-pressure clean the surfaces affected by fungi, also eliminating any traces of oil or grease, and wait for them to dry.

Seal any cracks and repair damaged parts.

The surfaces to be treated or any patches treated with repair mortars must complete the curing process, perfectly clean, cohesive and dry.



PROCLEAN

Preparing the product

PROCLEAN is ready to use, does not require dilution with water.

Application

Mix the product before use and apply it evenly, until it is no longer absorbed, in a single coating, using a brush, roller or spray gun.

PROCLEAN does not require any further washing treatments for removal, as it is compatible with Volteco preparation and finishing products.

For indoor application where it has not been possible to preventively pressure-wash to remove fungi deposits, wait for the first coat of PROCLEAN to dry, remove it with forceful brushing and then apply another coat of PROCLEAN.

Overapplication

Wait 2-3 hours before proceeding with applying PROFIX (see relative data sheet) or any other coating on top of it.



References available at www.volteco.com

CONSUMPTION AND YIELD

0.15 l/m² consumption can vary depending on the porosity and absorbency of the surface.

PACKAGING AND STORAGE

5 l or 20 l tanks.

The product must be stored in a dry place without being exposed to frost and heat (maximum temperature: 40 °C) or direct exposure to the sun before being applied.

Storage time 12 months.

WARNINGS - IMPORTANT NOTES

Do not apply the product on wet surfaces.

Do not apply the product to completely non-absorbent surfaces (e.g. metal, ceramic, existing waterproof coats).

Protect it from rain for at least 12 hours.

Brushes, rollers or spraying tools (airless) must be cleaned with water before the product dries.

The preparation and installation data refer to normal environmental conditions (temperature +20 °C; relative humidity 60%).

PHYSICAL AND TECHNICAL SPECIFICATIONS

Specification	Values
Appearance	Whitish liquid
Specific weight	1.1 kg/l
Viscosity (+20 °C ≠ 2-100 rpm)	20 mPa x s
Workability time at +20 °C	30'
Application temperature	+5 °C +30 °C

SAFETY

Refer to the related Safety Data Sheet.

COPYRIGHT

© Copyright Volteco S.p.A. - All rights reserved.

Information, images and text found in this document are exclusive property of Volteco S.p.A.

They may change anytime without prior notice.

Updated versions of this and other documentation (specification, brochure, other) are on www.volteco.com.

In case of translation text may contain technical and linguistic inaccuracies.

LEGAL NOTES

Note for buyer/installer:

This document prepared by Volteco S.p.A. is provided as an aid and guideline for the buyer/installer.



PROCLEAN

This does not take into consideration the details of each single operational context, for which Volteco S.p.A. will not be held liable.

This does not change and does not extend the obligations of Volteco S.p.A.

It may vary and the installer is therefore required to update his/her information prior to each application by referring to www.volteco.com.

The above clarifications extend to the pre-post-sales technical/commercial information of the commercial network.

