

PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 1 / 10

SECTION 1. Identification of the substance/preparation and of the company/undertaking

1.1 Product identifier

Name PAINT AIR

1.2. Identified relevant uses of the substance or mixture and non-recommended uses

Description/Use Paint with siloxane-resin base in emulsion for facades, with high water vapour permeability

1.3. Supplier information of the safety data sheet

Company Name VOLTECO Spa

Address Via delle Industrie, 47

District and Country 31050 Ponzano Veneto (TV) – IT

Telephone +39 0422 9663
Fax +39 0422 966401
e-mail address of the person in charge of the safety data sheet volteco@volteco.it

1.4. Emergency telephone number

For urgent enquiries, please contact +39 0422 9663

SECTION 2. Hazards identification

2.1 Classification of the substance or mixture

The product is not classified as dangerous pursuant to the provisions stipulated in EC Regulation No. 1272/2008 (CLP) as amended.

2.2 Label elements

Regulation EC No. 1272/2008 (CLP)

EUH208	May produce an allergic reaction. Contains: 2-octyl-2H-isothiazol-3-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3: 1)
Hazards identification	Not applicable.

Consigli di prudenza (S)

Not applicable.

Safety data sheet available on request for professional users.

2.3 Other hazards

The product does NOT contain substances that meet the PBT or vPvB criteria.

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3. Composition/information on ingredients

3.1 Substance/Mixture

Not applicable.

3.2 Mixture

Description Aqueous mixture with base of additives, loads and resins.

Components

None of the substances making up the mixture is above the values set out in Annex II of Regulation EC no. 1907/2006.

Name	CAS	EC	Conc. %	Classification 1272/2008/EC
Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3: 1) Reach Reg.: 01-2119475108-36-XXXX	55965-84-9	613-167-00-5	< 1%	Acute Tox. 2: H330 Acute Tox. 3: H301 Aquatic Acute 1: H400 Eye Dam. 1: H318 Skin corr. 1B: H314 Skin Sens. 1A: H317 - Danger
2-octyl-2H-isothiazol-3-one (1) Reach Reg.: 01-2120768921-45-XXXX	26530-20-1	247-761-7	< 1%	Acute Tox. 2: H330 Acute Tox. 3: H301+H311 Aquatic Chronic 1: H410 Eye Dam. 1: H318 Skin Corr. 1: H314 Skin Sens. 1A: H317 EUH071 - Danger



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 2 / 10

Name CAS EC Conc. % Classification 1272/2008/EC

(1) Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 To broaden the hazard information on substances, see Sections 11, 12 and 16.

Other information

Identification	M-factor
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	Acute 100
	Chronic: 100
Reaction mass of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2Hisothiazol-3-one (3:1) CAS: 55965-84-9 EC: Not applicable	Acute 100

Chronic: 100

Identification	Specific concentration limit
2-octyl-2H-isothiazol-3-one CAS: 26530-20-1 EC: 247-761-7	% (p\p) >=0.0015: Skin Sens. 1A-H317
Reaction mass of 5-chloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2Hisothiazol-3-one (3:1) CAS: 55965-84-9 FC: Not applicable	% (p\p) >=0.6: Skin Corr. 1B-H314 0.6<=%(p\p)<0.6: Skin Irrit. 2 - H315 % (p\p) >=0.06: Eye Irrit. 2 -H319 % (p\p) >=0.0015: Skin Sens. 1A-H317

SECTION 4. First aid measures

4.1 Description of the first aid measures

There are no known episodes of damage to staff appointed to use of the product.

Nevertheless, in case of need, the following general measures are taken.

Trever increes, in case of flood, and fellowing	onoral mododroo dro tartom
Contact with skin	In case of contact we recommend cleaning the affected area with plenty of water and neutral soap. In case of skin alterations (burning, reddening, rashes, blisters,), seek medical attention with this safety data sheet.
Contact with eyes	Take out any contact lenses. Wash immediately with plenty of water for at least 30/60 minutes, opening the eyelids well. Seek immediate medical attention.
Swallowing	Have him/her drink as much water as possible. Seek medical attention. Do not induce vomiting unless expressly authorised by the doctor.
Inhalation	Call a doctor right away. Take the injured individual outdoors, away from the site of the accident. If he/she stops breathing, perform CPR. Adopt suitable precautions for the first responder.

4.2 Main symptoms and effects, both acute and delayed

Refer to Chapter 2 and 11 for symptoms and effects caused by the contained substances.

4.3 Indication of any immediate medical attention and special treatment needed

Not applicable.

SECTION 5. Fire-fighting measures

5.1 Extinguishing agents

Suitable extinguishing agents	Non-flammable product, low risk of fire due to the flammability characteristics of the product under
	normal conditions of storage, handling and use. In the event of combustion following improper handling, storage or use, any type of extinguishing agent (ABC powder, water, etc.) can be used.
Unsuitable extinguishing agents	Not significant.

5.2 Special hazards arising from the substance or mixture

As a result of combustion or thermal decomposition, reaction sub-products are generated that can be highly toxic and therefore present a high health risk.

5.3 Recommendations for those in charge of putting out fires

Depending on the severity of the fire, it may be necessary to use complete protective clothing and self-contained breathing apparatuses. Set up a minimum emergency plant or elements for intervention (fireproof blankets, first aid kits, ...) in compliance with Directive



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 3 / 10

89/654/EC.

Additional equipment

Act in compliance with the Internal Emergency Plan and the Information Sheets on what to do in case of accidents and other emergencies. Eliminate any source of ignition. In case of fire, cool product storage vessels and tanks with a fire hazard, explosion hazard or BLEVE as a result of high temperatures. Avoid leaking products used for fire extinguishing into water.

SECTION 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For whoever is not working on it directly

Isolate spills as long as this does not pose an additional risk for the people performing this function.

In case of potential contact with spilled product, it is compulsory to use personal protective elements (see Paragraph 8).

Evacuate the area and keep people without protection away.

For whoever works on it directly

See Paragraph 8.

6.2 Environmental precautions

Prevent the product from entering the drains, surface water, ground water and confined areas as it contains substances that are dangerous for the environment.

Duly contain the absorbed product in airtight recipients.

Notify the competent authorities if substantial amounts of water are spilled.

6.3 Methods and materials for containment and cleaning up

We recommend:

Absorb the spillage with sand or absorbent inert material and move it to a safe place.

Do not absorb with sawdust or other inflammable absorbent material.

For any consideration regarding elimination, refer to Paragraph 13.

6.4 Reference to other sections

Any information on personal protection and disposal is found in Sections 8 and 13.

SECTION 7. Handling and storage

7.1 Precautions for safe handling	~

Precautions for safe handling	Fulfil legislation in force on safety in the workplace. Keep recipients hermetically closed. Control spills and residues, eliminating them safely (Paragraph 6). Avoid free spillage from the recipients. Keep the areas where hazardous products are handled clean and tidy.	
Technical recommendations for the prevention of fires and explosions	It is advisable to transfer slowly to avoid generating electrostatic discharges that could involve flammable products. Refer to Paragraph 10 on what conditions and materials to avoid.	
Technical recommendations to prevent ergonomic and toxicological risks	Avoid eating or drinking during handling and then be sure to wash with suitable products.	
Technical recommendations to prevent environmental risks	It is recommended to have absorbent material near the product (see Paragraph 6.3).	

7.2 Conditions for safe storage, including any incompatibility

7.2 Conditions for Sale Storage, including	g arry meompationity
Technical measures for storage	Minimum temperature: 5°C
	Maximum temperature: 30°C
	Maximum time: 6 months.
General conditions for storage	Avoid sources of heat, radiation, static electricity and contact with food. For further information see Paragraph 10.5.

7.3 Specific end uses

No particular use.

SECTION 8. Exposure control/personal protection

8.1 Control parameters

Substance with occupational exposure limit values that need to be controlled in the workplace.

There are not ambient limit values of the mixture.

DNEL (Workers)

Not applicable.

DNEL (Population)

Not applicable.



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 4 / 10

PNEC

Name of product/ingredient	Туре	Value	Environmental detail	Value
2-octyl-2H-isotiazol-3-one CAS: 26530-20-1 EC: 247-761-7	STP	Not applicable	Fresh water	0.0022 mg/l
	Soil	0.082 mg/kg	Sea water	0.00022 mg/l
	Intermittent	0.00122 mg/l	Sediment (fresh water)	0.0475 mg/kg
	Oral	Not applicable	Sediment (salt water)	0.00475 mg/kg

8.2 Exposure controls

General safety and hygiene measures for the work environment

As a prevention measure we recommend using basic personal protective equipment, marked with "CE seal".

For more information on personal protective equipment (storage, use, protection category, etc.) consult the information leaflet provided by the manufacturer of the PPE.

The indications contained in this point refer to the pure product.

The protection measures for the diluted product can vary based on its degree of dilution, use, application method, etc.

The regulation relative to the storage of chemical products, applicable for each case, will be taken into consideration to determine the obligation to install emergency showers and/or eye washes in the warehouses.

For more information read Paragraphs 7.1 and 7.2.

Respiratory protection

It will be necessary to use protective equipment if mist forms or if the occupational exposure limits are exceeded.

Hand protection

•				
Pictogram	DPI	Marked	ECN standards	Observations
Compulsory protection for the hands	Protective gloves against minor risks	CATI	EN 374-1:2003 EN 374-1:2003/AC:2006 EN 420:2003+A1:2009	Replace gloves at the first sign of deterioration. For periods of prolonged exposure to the product by professional / industrial users we recommend the use of CE III gloves in accordance with EN 420: 2004+ A1: 2010 and EN ISO 374-1: 2016 + A1: 2018.

As the product is a mixture of different materials, the resistance of the glove material cannot be reliably calculated in advance and has therefore to be checked prior to the application.

Eyes/face protection

Pictogram	DPI	Marked	ECN standards	Observations
Compulsory protection for the face	Panorama goggles against liquid droplets.	CATII	EN ISO 4007:2012	Clean daily and disinfect periodically in compliance with the manufacturer's instructions.

ECN standards

Observations

Marked

Body protection Pictogram

 		 0.000.144.00
Non-slip work shoes	CATII	Replace if there is any sign of deterioration. For prolonged exposure periods for professional / industrial users, CE III is recommended, according to EN ISO 20345: 2012 and EN 13832-1: 2007 standards
Work clothes	CATI	Replace if there is any sign of deterioration. For prolonged exposure periods for professional / industrial users, CE III is recommended, according to EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 5 / 10

Complementary emergency measures

Emergency measures	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011 ISO 3864-4:2011
Eve bath	DIN 12 899 ISO 3864-1:2011 ISO 3864-4:2011

Environmental exposure controls

Based on Community legislation on environmental protection we recommend against releasing the product and its containers in the environment.

For further information see Paragraph 7.1.D.

Volatile organic compounds

In application of Directive 2010/75/EU, this product presents the following characteristics:

V.O.C. (Supply): 0 % in weight

V.O.C. density at 20 °C: 0 kg/m3 (0 g/l)

Mean carbon number: 5.86

Mean molecular weight: 114.22 g/mol

SECTION 9. Physical and chemical properties

9.1 Information on the basic physical and chemical properties

Description	Values
Physical state	Liquid
Appearance	Dense
Colour	As indicated in the container
Odour	Characteristic
Olfactory threshold	Not applicable
pH	ca. 8
Melting or freezing point	Not applicable
Initial boiling point	100°C
Flash point	Not flammable (> 60°C)
Flammability of solids and gases	Not applicable
Evaporation rate	Not applicable
Lower flammability limit	Not applicable
Upper flammability limit	Not applicable
Lower explosivity limit	Not applicable
Upper explosivity limit	Not applicable
Vapour pressure at 20 °C	2350 Pa
Vapour pressure at 50 °C	12379.99 Pa
Density at 20 °C	1637 kg/m³
Relative density at 20 °C	1.637
Solubility	Not applicable
Partition coefficient n-octanol/water	Not applicable
Oxidising properties	Not applicable
Explosive properties	Not applicable
Decomposition temperature	Not applicable
Auto-ignition temperature	292°C
Kinematic viscosity at 40 °C	Not applicable
Kinematic viscosity at 20 °C	Not applicable
Dynamic viscosity at 20 °C	Not applicable
9.2 Other information	



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 6 / 10

Surface tension at 20°C: Not applicable

Refraction index: Not applicable

Corrosive substances or mixtures for metals: Not applicable

Heat of combustion: Not applicable

Aerosol-total percentage (by mass) of flammable components: Not applicable

SECTION 10. Stability and reactivity

10.1 Reactivity

There are no particular hazards of reaction with other substances under normal conditions of use.

See Section 7.

10.2 Chemical stability

The product is stable under normal conditions of use and storage.

10.3 Possibility of hazardous reactions

No dangerous reactions are expected under normal conditions of use and storage.

10.4 Conditions to be avoided

Applicable to handling and storage at ambient temperature:

Shock and friction	Not applicable
Contact with air	Not applicable
Heating	Not applicable
Sun light	Not applicable
Humidity	Not applicable

10.5 Incompatible materials

Acids	Avoid strong acids.
Water	Not applicable
Oxidising materials	Avoid direct impact
Combustible materials	Not applicable

Other Avoid alkalis and strong bases

10.6 Hazardous decomposition products

See heading 10.3, 10.4 and 10.5 to specifically know the decomposition products.

Depending on the conditions of decomposition, this may lead to the release of complex mixtures of chemical substances: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11. Toxicological information

11.1 Information on toxicological effects

There is no experimental data available on the product as such in relation to the toxicological properties.

Dangerous effects for health

Repeated, prolonged exposure or at higher concentrations than established for the occupational exposure limits, may produce harmful effects on health based on the channel of exposure:

Ingestion (acute effect)	Acute toxicity: Based on the available data the classification criteria is not fulfilled, nevertheless it presents substances classified as hazardous for ingestion. For further information see Paragraph 3. Corrosivity/Irritability: Based on the available data the classification criteria is not fulfilled, nevertheless it presents substances classified as hazardous for this effect. For further information see Paragraph 3.
Inhalation (acute effect)	Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see Paragraph. 3 Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
Contact with skin and eyes (acute effect)	Contact with skin: Based on the available data the classification criteria is not fulfilled, nevertheless it presents substances classified as hazardous for contact with the skin. For further information see Paragraph 3. Contact with eyes: Based on the available data the classification criteria is not fulfilled, nevertheless it presents substances classified as hazardous for this effect. For further information see Paragraph 3.
CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)	Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see Paragraph 3 IARC: n-butyl acrylate (3)

Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain

Methyl methacrylate (3)



Effects of sensitisation

VOLTECO Spa

PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 7 / 10

substances classified as hazardous for this effect. For more information see Paragraph 3.

Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see Paragraph 3.

Breathing apparatuses: Based on the available data the classification criteria is not fulfilled, as it does

not present substances classified as hazardous with sensitising effects. For further information see Paragraph 3.

Dermal: Based on the available data the classification criteria is not fulfilled, nevertheless it presents

substances classified as hazardous with sensitising effects. For further information see Paragraph 3.

Specific toxicity for target organs (STOT) -Based on the available data the classification criteria is not fulfilled, as it does not present substances classified as hazardous for ingestion. For more information see Paragraph 3.

Specific toxicity for target organs (STOT) - Basandosi sui dati disponibili i criteri di classificazione non sono soddisfatti, poiché non presenta sostanze classificate come pericolose per questo effetto. Per maggiori informazioni vedere Paragrafo

Pelle: Basandosi sui dati disponibili i criteri di classificazione non sono soddisfatti, poiché non presenta sostanze classificate come pericolose per questo effetto. Per maggiori informazioni leggere Paragrafo

Risk if inhaledBased on the available data the classification criteria is not fulfilled, as it does not present substances classified as hazardous for this effect. For more information see Paragraph 3.

Other information

Identification	-	-	Acute toxicity	-	-
Name of product/ingredient	CAS	EC	Туре	Dose	Туре
Reaction mass of 5-chlor o-2-methyl-2H- isothiazol-3-one and 2-m ethyl-2Hisothiazol-3-one (3:1)		Not applicable	LD50 Oral	64 mg/kg	Rat
			LD50 Dermal	87.12 mg/kg	Rabbit
			CL50 Inhalation	0.33 mg/l (4h)	Rat
2-octyl-2H- isothiazol-3-one	26530-20-1	247-761-7	LD50 Oral	125 mg/kg	
			LD50 Dermal	311 mg/kg	
			CL50 Inhalation	Not applicable	

11.2 Information on other hazards Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information Not applicable.

SECTION 12. Ecological information

There is no available data on the mixture.

12.1 Toxicity Acute toxicity

Name of product/ingredient	CAS	EC	Туре	Dose	Exposure	Туре
Reaction mass of 5-c hloro-2-methyl-2H- isothiazol-3-one and 2-methyl-2Hisothiazo l-3-one (3:1)		Not applicable	CL50	> 0.1-1	96 h	Fish
			EC50	> 0.1-1	48 h	Crustace
			EC50	> 0.1-1	72 h	Algae
2-octyl-2H- isothiazol-3-one	26530-20-1	247-761-7	CL50	> 0.1-1	96 h	Fish
			EC50	> 0.1-1	72 h	Algae
			EC50	> 0.1-1	48 h	Crustace

12.2 Persistence and degradability



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 8 / 10

No data available.

12.3 Bioaccumulative potential

No data available.

12.4 Mobility in the soil

No data available.

12.5 Results of the PBT and vPvB evaluation

Based on available data, the product does not contain PBT or vPvB substances.

12.6 Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects

Not described.

SECTION 13. Disposal considerations

13.1 Waste processing methods

Code	•	Type of residue (EC Regulation No. 1357/2014)
08 01 12	Waste paints, other than those in item 08 01 11	Not dangerous

Type of residue (EU Regulation No. 1357/2014)

Not applicable.

Waste management (elimination and valorisation)

Consult the residue manager authorised to perform valorisation and elimination operations in compliance with Annex 1 and Annex 2 (Directive 2008/98/EC, Legislative Decree 205/2010). According to Codes 15 01 (2014/955/EU), if the container has been in direct contact with the product it will treated in the same way as the product itself, otherwise it will be treated as non-hazardous residue. Do not dispose of into watercourses. See Point 6.2.

Provisions regarding waste management

In conformity with Annex II of EC Regulation No. 1907/2006 (REACH) the Community or state provisions pertaining to waste management are implemented. Community legislation: Directive 2008/98/EC, 2014/955/EU, EU Regulation No. 1357/2014. National legislation: Legislative Decree 25/2010.

SECTION 14. Transport information

The product is not classified as dangerous in accordance with the provisions in force concerning transport of dangerous goods by road (ADR) and by Rail (RID), by sea (IMDG Code) and by air (IATA).

SECTION 15. Regulatory information

15.1 Specific standards and regulations on health, safety and environment for the substance or mixture Regulation EC No. 528/2012

Contains a preservative to maintain the original properties of the treated item.

Contains Tetrahydro-1,3,4,6-tetrakis (hydroxymethyl) imidazo [4,5-d] imidazole-2,5 (1H, 3H) -dione, reaction mass of 5-chloro-2-methyl-2Hisothiazol- 3-one and 2-methyl-2H-isothiazol-3-one (3: 1), bronopol (DCI), 1,2-benzisothiazol-3 (2H) -one, 2-methyl-2H-isothiazol-3-one, diuron (ISO), Zinc pyrithione, 2-octyl-2H-isothiazol-3-one

Substances subject to authorisation Regulation EC No. 1907/2006 (REACH)

Not applicable.

Substances included in Annex XIV of REACH (authorisation list) and expiration date

Not applicable.

Regulation EC No. 1005/2009 on substances that reduce the ozone layer

Not applicable.

Art. 95, EU Regulation no. 528/2012

Reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2Hisothiazol-3-one (3:1) (Product type 2, 4, 6, 11, 12, 13); 2-octyl-2H-isotiazol-3-one (Product type 6, 7, 8, 9, 10, 11, 13)

Regulation EU No. 649/2012 on exporting and importing hazardous chemical substances

Not applicable.

Seveso III

Not applicable.

Restrictions on the sale and use of certain hazardous substances and mixtures (Annex XVII, REACH)

Not applicable.



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 9 / 10

Special provisions regarding the protection of people or the environment

We recommend using the information provided in this safety data sheet as the input data in an assessment of the risks of local circumstances with the aim of establishing the necessary risk prevention measures for handling, use, storage and elimination of said product.

Other legislations

Lgs. D. No. 205/2010

Provisions for the implementation of Directive No. 2008/98/EC of the European Parliament and Council of 19 November 2008 on waste and repealing certain Directives.

D. Lgs. n. 85/2016

Regulation laying down rules for the implementation of Directive 2014/34 / EU on the harmonization of the laws of the Member States relating to equipment and protective systems intended for use in potentially explosive atmospheres.

Lgs. D. No. 233/2003

Implementation of Directive 1999/92/EC relative to the minimum requirements for the improvement of the protection of the safety and health of workers exposed to the risk of explosive atmospheres.

Lqs. D. No. 186/2011

Rules of penalties for the violation of provisions of EC Regulation No. 1272/2008.

D. Lgs. n. 161/2006

Implementation of Directive 2004/42 / EC, for the limitation of volatile organic compound emissions resulting from the use of solvents in certain paints and varnishes, as well as in bodywork products.

D. Lgs. n. 152/2006

Environmental regulations. Royal decree 147/1927, last updated 06/12/2021. Approval of the special regulation for the use of toxic gases. G.U. 14 March 2016 n. 61 - Legislative Decree no. 39 of 15 February 2016

Consolidated text on health and safety at work - Rev. 2022

15.2 Chemical safety assessment

No chemical safety assessment has been conducted for the mixture and the substances contained in it.

SECTION 16. Other information

Applicable legislation to safety data sheets

This safety data sheet was developed in compliance with Annex II - Guide to the compilation of Safety Data Sheets of EC Regulation No. 1907/2006 - EC Regulation No. 453/2010 - EU Regulation No. 878/2020 of the Commission.

Modifications in relation to the previous safety data sheet on risk management measures

Composition/information on ingredients (Section 3):

Withdrawn substances: n-butyl acrylate (141-32-2); Ethylene glycol (107-21-1); Methyl methacrylate (80-62-6); Zinc pyrithione (13463-41-7); Pyridine 1-oxide -2-thiol; Sodium salt (3811-73-2)

Regulation EC No. 1272/2008 (CLP) (Section 2, Section 16)

- Hazard statements
- Precautionary tips

Texts of legislative phrases covered in Section 0

The phrases stated here do not refer to the product itself, they are provided by way of example and refer to the single components that appear in Section 3.

Regulation EC No. 1272/2008 (CLP)

• • • • • • • • • • • • • • • • • • • •		
H310+H330	Acute Tox. 2	Fatal in contact with skin or if inhaled
H330	Acute Tox. 2	Lethal if inhaled
H301	Acute Tox. 3	Toxic if swallowed
H301+H311	Acute Tox. 3	Toxic if swallowed or in contact with skin
H400	Aquatic Acute 1	Very toxic to aquatic organisms
H410	Aquatic Chronic 1	Very toxic to aquatic life with long-term effects
H318	Eye Dam. 1	Causes serious eye damage
H314	Skin Corr. 1	Causes severe skin burns and eye damage
H314	Skin Corr. 1B	Causes severe skin burns and eye damage
H317	Skin Sens. 1A	May cause an allergic skin reaction

Classification procedure

Not applicable.

Tips on training

We recommend minimum training on the topic of work risk prevention for staff who will be handling this product, with the aim of facilitating the comprehension and interpretation of this safety data sheet, as well as product labelling.



PAINT AIR

Revision n. 4.0

Revision date 23/09/2022

Printed on 23/09/2022

Page nr. 10 / 10

Main sources of literature

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms

- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- IMDG: International maritime code for transport of Dangerous Goods
- IATA: International Air transport Association
- ICAO: International Civil Aviation Organization
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bio-concentration factor
- Lethal dose for 50% of the test population
- LC50: Lethal concentration for 50% of the test population
- EC50: Effective concentration 50%
- Log POW: Octanol-water partition coefficient logarithm
- Koc: Soil organic carbon-water partitioning coefficient
- UFI: Unique formula identifier
- IARC: International Agency for Research on Cancer