








PRODUCT CATALOGUE






It's a waterproof life.

Categories

WATERPROOFING

- | | | |
|-----------------------------------------------------------------------------------|--------------------------------------------|--------|
|  | Synthetic hydro-reactive membranes | pg. 9 |
|  | Bentonite hydro-reactive membranes | pg. 11 |
|  | Flexible liquid systems | pg. 12 |
|  | Waterproof mortars - Rapid-setting mortars | pg. 15 |
|  | Primers - Paints | pg. 17 |



JOINTS AND SEALANTS

- | | | |
|-------------------------------------------------------------------------------------|------------------------------------------------|--------|
|  | Waterstops - Hydro-expanding mastics | pg. 21 |
|  | Joint covers - Profiles - Reinforcement meshes | pg. 24 |
|  | Adhesives - Anchors - Mastics | pg. 27 |

DAMP-PROOF RENOVATION

- | | | |
|-------------------------------------------------------------------------------------|--------------------------------|--------|
|  | Damp-proof restoration systems | pg. 31 |
|-------------------------------------------------------------------------------------|--------------------------------|--------|






RECOVERY AND PROTECTION

- | | | |
|-------------------------------------------------------------------------------------|---------------------------------------------------|--------|
|  | Repair mortars | pg. 35 |
|  | Waterproof levelling compounds - Primers - Paints | pg. 37 |

WORK TOOLS

pg. 41


Product index

	AKTI-VO 201	pg. 22
	AKTI-VO BS	pg. 22
	AMPHIBIA 3000 / AMPHIBIA 3000 GRIP	pg. 9
	AMPHIBIA ACCESSORI	pg. 9 - 10
	AQUASCUD SYSTEM 420 / AQUASCUD SYSTEM 430	pg. 12
	AQUASCUD REFLEX	pg. 12
	AQUASCUD LINE	pg. 25
	AQUASCUD JOIN BT / AQUASCUD JOIN	pg. 24
	BI FIX 300	pg. 27
	BI FLEX SYSTEM	pg. 24
	BI BOND	pg. 27
	BI MASTIC	pg. 7
	BI MORTAR CONCRETE SEAL	pg. 15
	BI MORTAR PLASTER SEAL	pg. 15
	BI MORTAR RASO SEAL	pg. 15
	BI MORTAR SL	pg. 15
	BREAK	pg. 21
	CALIBRO NHL	pg. 31
	CALIBRO PLUS EVAPORATION/RINZAFFO	pg. 31
	CARBON STEEL CONNECTORS	pg. 27
	CP1	pg. 37
	CPØ	pg. 37
	CRYSTAL POOL	pg. 17
	CRYSTAL	pg. 17
	FIBRO HFR	pg. 35
	FIBROeRASO	pg. 35

	FIBROMIX 40	pg. 35
	FLEXOMIX 30	pg. 36
	FLEXONET	pg. 25
	FLOWMIX 70	pg. 36
	GARVO ANGOLARE	pg. 13
	GARVO 3 / GARVO 5	pg. 24
	GRIPPER	pg. 13
	I-PLUG	pg. 15
	PAINT AIR / PAINT PROTECTION	pg. 39
	PLASTIVO 180 / PLASTIVO 250	pg. 12
	PROCLEAN	pg. 38
	PROFIX 20 / PROFIX 30/ PROFIX 40	pg. 38-39
	PROFIX 60	pg. 17
	PROFIX 80	pg. 17
	REPOSOL	pg. 28
	REVOMAT	pg. 25
	SANOFER	pg. 35
	SPIDY 15	pg. 16
	TAP 3	pg. 16
	TRIPLEZERO	pg. 32
	TRIPLEZERO - T	pg. 32
	VOLGRIP LH / VOLGRIP HP/ VOLGRIP EP	pg. 11
	VOL-TEC	pg. 23
	WT	pg. 21
	X-LIME	pg. 31
	XNET	pg. 25

It's a waterproof life.

WATERPROOFING



WATERPROOFING



pg. 12

Flexible liquid systems



pg. 15

**Waterproof mortars -
Rapid-setting mortars**



**Primers
Paints**



pg. 17



pg. 9









**Synthetic and Bentonite
hydro-reactive membranes**




It's a waterproof life.


Synthetic hydro-reactive membranes




CODE	PRODUCT DESCRIPTION	m ² /ROLL	N. OF ROLLS FOR PALLET	m ² /PALLET	HS CODE
	 <p>AMPHIBIA 3000 GRIP HYDRO-REACTIVE MULTI-LAYER WATERPROOFING MEMBRANE</p> <ul style="list-style-type: none"> > Absolute impermeability with no side seepage of water > Immediate mechanical protection, self-repairing also on accidental holes > High resistance to hydraulic load > High flexibility and capacity to bridge cracks <p>CE UNI EN 13967 BBA - (N° 20/5771) ETN 03/23 EPD 0299</p>   				
RA02	<p>AMPHIBIA 3000 H. 1.80 size: 180x2000 cm pallet size: 190x120x130 cm</p>	36	20 ROLLS	720	40051000
RA04	<p>AMPHIBIA 3000 H. 90 size: 90x1000 cm pallet size: 120x100x125 cm</p>	9	36 ROLLS	324	40051000
	 <p>AMPHIBIA 3000 GRIP 1.3 HYDRO-REACTIVE MULTI-LAYER WATERPROOFING MEMBRANE</p> <ul style="list-style-type: none"> > Absolute impermeability with no side seepage of water > Immediate mechanical protection, self-repairing also on accidental holes > High resistance to hydraulic load > High flexibility and capacity to bridge cracks <p>CE UNI EN 13967 BBA - (N° 20/5771) ETN 03/23 EPD 0299</p>   				
RA15	<p>AMPHIBIA 3000 GRIP 1.3 H. 1.80 size: 180x2000 cm pallet size: 190x120x130 cm</p>	36	20 ROLLS	720	40051000
RA16	<p>AMPHIBIA 3000 1.3 H. 90 size: 90x1000 cm pallet size: 120x100x125 cm</p>	9	36 ROLLS	324	40051000


Accessories

CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	m/TUBE	HS CODE
RB01	 AMPHIBIA PRESSURE LINE METALLIC PROFILE, COATED ON ONE SIDE WITH AMPHIBIA 3000 - size: 150x5 cm	CARDBOARD TUBE	PCS. 30x1,5 m	45	40051000


RB02	 AMPHIBIA PRESSURE CORNER CORNER METALLIC PROFILE COATED WITH AMPHIBIA 3000 MEMBRANE - size: 150x5x10 cm	CARDBOARD TUBE	PCS. 7x1,5 m	10,5	40051000
RB03	CORNER 90° CORNER METALLIC PROFILE COATED WITH AMPHIBIA 3000 MEMBRANE AND ADHESIVE BUTYLIC TAPE AMPHIBIA SAFETY TAPE BT - size: 150x5x10 cm				

CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	-	HS CODE
RB05	 AMPHIBIA SAFETY TAPE ADHESIVE TAPE FOR OVERLAPPING PROTECTION WHITE COLOUR - size: 6x2500 cm	ROLL 25 m	1 PC.	-	40023100



RB08	 AMPHIBIA LAP SEAL BUTYL ADHESIVE TAPE FOR OVERLAPPING SEALING GAS size: 6x1000 cm	ROLL 10 m	1 PC.	-	56031410
------	--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	--------------	-------	---	----------

RB04	 AMPHIBIA STOPPER PROTECTION CAP FOR CLOSING HOLES FORMWORK, BLACK COLOUR	BAG	50 PCS.	-	39201000
------	------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-----	---------	---	----------

RB09	 AMPHIBIA 3000 STRIP TAPE OF AMPHIBIA 3000 MEMBRANE size: 12x1850 cm	ROLL 18,5 m	1 PC.	-	40029910
------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------	----------------	-------	---	----------



CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	cc/PACK	HS CODE
GB12	 AKTI-VO 201 SYNTHETIC RUBBER HYDRO-EXPANDING MASTIC 320 CC CARTRIDGES	BOX	PCS. 6	320	32141010



RB11	 BI MASTIC DEFORMABLE ADHESIVE MASTIC WITH HIGH PERFORMANCE	BOX	PCS. 10	600	32149000
------	----------------------------------------------------------------------------------------------------------------------------------------------------------	-----	---------	-----	----------



CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	kg/PALLET	HS CODE
AC044	 AKTI-VO BS MASTIC COMPOSED OF NATURAL SODIUM BENTONITE AND BUTYL RUBBER	BOX	10 PCS.	600 cc/UNIPACK	3214101000
AC045	 AKTI-VO BS MASTIC COMPOSED OF NATURAL SODIUM BENTONITE AND BUTYL RUBBER	PAIL	20 kg	-	3214101000

Bentonite hydro-reactive membranes






CODE	PRODUCT DESCRIPTION	m ² /ROLL	PACKAGING	m ² /PALLET	HS CODE
	 VOLGRIP LH BENTONITE-BASED WATERPROOF MEMBRANE SELF-FASTENING TO CONCRETE > Natural-based product , it earns points for LEED certification > Insuperable self-confinement > High impermeability > It can be drilled, cut and shaped to adapt to the structure  UNI EN 13491				
AO01	VOLGRIP LH H. 2.50 (LIGHT) size: 250x3000x0,64 cm - weight 5,4 kg/m ² approx	75	ROLL	-	6815990000
AO02	VOLGRIP LH H. 5.00 (LIGHT) size: 250x3000x0,64 cm - weight 5,4 kg/m ² approx	150	ROLL	-	6815990000
AO03	VOLGRIP LH H. 1.10 (LIGHT) size: 110x500x0,64 cm - weight 5,4 kg/m ² approx (960 kg/pallet)	5,50	BOX	192,50	6815990000

	 VOLGRIP HP BENTONITE-BASED WATERPROOF MEMBRANE SELF-FASTENING TO CONCRETE WITH INTEGRATED POLYETHYLENE SHEET > Insuperable self-confinement > High impermeability even in difficult sites and in the presence of water with high salinity or polluted > It can be drilled, cut and shaped to adapt to the structure > Natural-based product , it earns points for LEED certification  UNI EN 13491				
AP01	VOLGRIP HP H. 2.50 (HIGH PERFORMANCE) size: 250x3000x0,64 cm - weight 5,0 kg/m ² approx	75	ROLL	-	6815990000
AP02	VOLGRIP HP H. 5.00 (HIGH PERFORMANCE) size: 250x3000x0,64 cm - weight 5,0 kg/m ² approx	150	ROLL	-	6815990000






	 VOLGRIP EP BENTONITE - BASED WATERPROOF GEO MEMBRANE FOR ENVIRONMENTAL PROTECTION > Natural-based product , it earns points for LEED certification > It can be drilled, cut and shaped to adapt to the structure > High impermeability even in difficult sites and in the presence of water with high salinity or polluted > Insuperable self-confinement  UNI EN 13361 UNI EN 13362 UNI EN 13492 UNI EN 13493 UNI EN 13382				
AR01	VOLGRIP EP size: 500x3000x0,64 cm - weight 5,0 kg/m ² approx	150	ROLL	-	6815990000

Accessories














CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	kg/PALLET	HS CODE
AC042	 VOLGROUT SODIUM BENTONITE FOR INJECTIONS	BAG	4 kg	480	25081000
DB04	 SALINE SEAL GRANULAR SODIUM BENTONITE ADDITIVATED WITH POLYMERS	BAG	25 kg	1000	25081000
CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	USE/m ²	HS CODE
AD051	 FIX 1 - POLYETHYLENE WASHER AND TEMPERED STEEL NAILS size: washer Ø mm 50 - steel nail: lenght mm 30	BOX	500 PCS.	3 PCS.	39201000
AD053	FIX 5 - POLYETHYLENE WASHER size: washer Ø mm 50	BOX	500 PCS.	3 PCS.	392012090

Flexible liquid systems



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	m²/PALLET	HS CODE
	PLASTIVO 180 TWO-COMPONENT FLEXIBLE WATERPROOFING COMPOUND > Fast curing allowing for short waiting times between the first and second coat and subsequent tiling, even under low temperature conditions (all in 24 hours) > Suitable for application on damp substrates > Suitable for contact with drinking water > Resistant to negative hydrostatic pressure  				
EH25	15 kg powder + 5 kg liquid cod. ZH001 15 kg powder cod. ZZEH2 5 kg liquid	3~3,5 kg/m²	BAG + PAIL 20 kg	1600	38245090
	PLASTIVO 250 TWO-COMPONENT FLEXIBLE WATERPROOFING COMPOUND > High flexibility > Complete waterproofing cycle within one day > Suitable for contact with drinking water > Suitable for contact with purifier water and domestic wastewater 				
EM01	14 kg powder + 6,6 kg liquid cod. ZM001 14 kg powder cod. ZZM1 6,6 kg liquid	3,5~4 kg/m²	BAG + PAIL 20,6 kg	1648	38245090
	AQUASCUD SYSTEM 420 TWO-COMPONENT WATERPROOFING PRODUCT > Fast drying even in low temperature conditions (all within 24 hours) > For waterproofing without demolition . > Low environmental impact thanks to reduced CO2 emissions 				
CB06	15 kg powder + 5,7 kg liquid cod. ZD004 15 kg powder cod. ZZD5 5,7 kg liquid	3,6~4 kg/m²	BAG + PAIL 20,7 kg	1656	38245090
	AQUASCUD SYSTEM 430 TWO-COMPONENT WATERPROOFING PRODUCT > It maintains deformability to -20°C > For waterproofing without demolition . > Resistant to UV radiation > Low environmental impact thanks to reduced CO2 emissions 				
CB07	12 kg powder + 6 kg liquid cod. ZD005 12 kg powder cod. ZZD6 6 kg liquid	3,2~3,5 kg/m²	BAG + PAIL 18 kg	1440	38245090
	AQUASCUD REFLEX READY TO USE REFLECTING WATERPROOF COATING > Excellent resistance to UV radiation > High waterproof performances & crack bridging ability > Suitable for application on bituminous, cementitious membranes and concrete screeds				
CB11	AQUASCUD REFLEX	0,6~0,7 kg/m²	VASE 16 kg	-	32091000

Accessories







CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	m²/PALLET	HS CODE
CC01	 AQUASCUD BASIC MICROPOROUS ELASTICIZED WATER-REPELLENT FLEECE 30 m² boxes (30x1 m)	BOX	30 mq	960	56031290
CB09	 GRIPPER SKID-PROOF WALKABLE FINISHING POWDER GREY COLOUR ○	BOX	10 KG	-	25059000
CB10	SPECIAL COLOURS AVAILABLE: BROWN ORANGE LIGHT BLUE				
CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	WIDTH	HS CODE
EE01	 GARVO due JOINT COVER STRIP REINFORCED WITH THERMO-PLASTIC RUBBER	BOX	25 m	8,5 cm	63079098
ED142	 GARVO 3 JOINT COVER STRIP REINFORCED WITH RUBBER	BOX	20 m	10 cm	63079098
ED141	 GARVO 5 JOINT COVER STRIP REINFORCED WITH RUBBER	BOX	20 m	15 cm	63079098
CD01	 AQUASCUD JOIN ELASTICIZED JOINT COVER BAND	BOX	25 m	10 cm	63079098
CD04	 AQUASCUD JOIN BT ELASTICIZED JOINT COVER BAND WITH ADHESIVE BUTYL RUBBER	BOX	20 m	10 cm	56031410
CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	DIMENSION	HS CODE
	AQUASCUD JOIN BT ANGULAR PRE-SHAPED BAND COVER, WITH ADHESIVE BUTYL RUBBER	BOX	10 PCS.	12x12 cm	56031410
CD05	 ANGULAR 90°				
CD06	 ANGULAR 270°			10,5x10,5 cm	
	GARVO ANGULAR FELT-COATED RUBBER	BOX	10 PCS.	12x12 cm	63079098
ED144	 ANGULAR 90°				
ED145	 ANGULAR 270°			12x12 cm	
	EXHAUST/DRAINAGE FELT-COATED RUBBER	BOX	2 PCS.	25x25 cm	39219090
CE04	 EXHAUST/DRAINAGE PIPE Ø80 exhaust/drainage pipe: Ø 72 mm pipe size: Ø 80xh23 cm				
CE02	EXHAUST/DRAINAGE PIPE Ø100 Exhaust/drainage pipe Ø 92 mm pipe size: Ø 100xh23 cm				
CE03	 GARVO QUADRO JOINT COVER STRIP REINFORCED WITH RUBBER	-	1 PC.	40x40 cm	39219090

Accessories

CODE	PRODUCT DESCRIPTION	PACKAGING CONTENT	QUANTITY	HS CODE
CF09	AQUASCUD H.0 LINE EDGING PROFILE WITH DRAINAGE size: 270x8x5,5 cm	BOX	1 PC. 2,7 m	76041090
	GREY COLOUR <input type="radio"/>			
CF12	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CF01	AQUASCUD H.10 LINE EDGING PROFILE WITH DOUBLE DRAINAGE size: 270x9x6,5 cm	BOX	1 PC. 2,7 m	76041090
	GREY COLOUR <input type="radio"/>			
CF04	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CODE	PRODUCT DESCRIPTION	CONTENT	QUANTITY	HS CODE
CF11	AQUASCUD H.0 CORNER 90° CORNER PROFILE FOR AQUASCUD H.0 LINE size: 21x21x5,5 cm	-	1 PC.	76041090
	GREY COLOUR <input type="radio"/>			
CF14	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CF10	AQUASCUD H.0 FIXY CONJUNCTION PROFILE FOR AQUASCUD H.0 LINE	BAG	1 PC.	76041090
	GREY COLOUR <input type="radio"/>			
CF13	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CF03	AQUASCUD H.10 CORNER 90° CORNER PROFILE FOR AQUASCUD H.10 LINE size: 21x21x6,5 cm	-	1 PC.	76041090
	GREY COLOUR <input type="radio"/>			
CF06	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CF07	AQUASCUD H.10 CORNER 270° CORNER PROFILE FOR AQUASCUD H.10 LINE size: 21x21x6,5 cm	-	1 PC.	76041090
	GREY COLOUR <input type="radio"/>			
CF08	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			
CF02	AQUASCUD H.10 FIXY CONJUNCTION PROFILE FOR AQUASCUD H.10 LINE	BAG	1 PC.	76041090
	GREY COLOUR <input type="radio"/>			
CF05	SPECIAL COLOURS AVAILABLE: <input type="radio"/> WHITE <input type="radio"/> BROWN <input type="radio"/> ANTHRACITE <input type="radio"/> COR-TEN			




Waterproof mortars - Rapid-setting mortars



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
	BI MORTAR CONCRETE SEAL CEMENT-BASED WATERPROOFING COATING APPLICABLE BY BRUSH > Suitable for both indoor and outdoor application > Particularly resistant to abrasion and impact > Suitable for continuous contact with water > Easy maintenance , also in conditions of high humidity and closed environments  UNI EN 1504-2 PRINCIPI PI, MC e IR				
	IL04	BI MORTAR CONCRETE SEAL	2,5~3,0 kg/m ²	BAG kg 20	1200
	BI MORTAR RASO SEAL LEVELLING FIBRE-REINFORCED WHITE COMPOUND WITH WATERPROOFING AND FINISHING FUNCTION > Good surface finish thanks to its fine grain size > Waterproof levelling compound also suitable in conditions of negative hydraulic pressure > Excellent adhesion on most types of substrates such as concrete, mortar, stone, brick > It simplifies and reduces the application phases as it evens out and waterproofs in a single application				
	IL07	BI MORTAR RASO SEAL 20 kg powder + 5 kg liquid cod. ZIL01 20 kg powder cod. ZIL1 5 kg liquid	1,85 kg/m ² each mm of thickness	BAG+VASE kg 25	1500
	BI MORTAR PLASTER SEAL FIBRE-REINFORCED WATERPROOFING PLASTER > It simplifies and reduces the application phases as it evens out and waterproofs in a single application > Also applicable on uneven surfaces > Excellent adhesion > Excellent resistance to negative pressure				
	IL01	BI MORTAR PLASTER SEAL	18 kg/m ² each mm of thickness	BAG kg 25	1200
	BI MORTAR SL WATERPROOF PLASTER MORTAR, CONTROLLED SHRINKAGE > It simplifies and reduces the application phases as it reinforces and waterproofs in a single application > It can be mixed with fine gravel when applying high thick casting > Excellent resistance to negative pressure > Suitable for both indoor and outdoor application				
	IL02	BI MORTAR SL	17 kg/m ² each mm of thickness	BAG kg 25	1250
	I-PLUG ULTRA-RAPID WATERPROOF MORTAR > Excellent waterproofing > No shrinkage > Instantaneously block water flows , even if pressurised > High mechanical resistance				
	IC186	I-PLUG	10 kg yields 6 liters of mortar	BAG kg 10	800

Waterproof mortars - Rapid-setting mortars



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
	TAP 3 WATERPROOF QUICK-SETTING HYDRAULIC MORTAR > Excellent waterproofing > Rapid-setting > No shrinkage > High mechanical resistance				
	IC181 TAP 3 - 5 kg	5 kg yields 3 liters of mortar	BOX kg 5	600	38245090
	TAP 3 WATERPROOF QUICK-SETTING HYDRAULIC MORTAR > Excellent waterproofing > Rapid-setting > No shrinkage > High mechanical resistance				
	IC182 TAP 3 - 20 kg	20 kg yields 12 liters of mortar	PAIL kg 20	600	38245090
	SPIDY 15 WATERPROOF QUICK-SETTING MORTAR > Good finish results > High adhesion to concrete and reinforcement bars > Rapid-setting also on surfaces and in particularly damp environments > Excellent thixotropy that does not require the use of formwork				
	FH01 SPIDY 15	19 kg/m ² each cm of thickness	BAG 15 kg	1200	38245090



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	-	HS CODE
	PROFIX 60 TWO-COMPONENT EPOXY RESIN BASED PRIMER > It adjusts surface absorption > Suitable for installation , even in the presence of damp > To reduce vapour passage > Removes dust from cement-based surfaces				
	EX01 TAP 3 - 5 kg Two components	0,25÷0,30 kg/m ² (5 kg + 2,5 kg)	VASE + VASE kg 7,5	-	39073000
	PROFIX 80 THREE-COMPONENT EPOXY CEMENT BASED ANCHORING PRIMER > Suitable for installation , even in the presence of damp > Anchoring capacity > Waterproof				
	EN07 PROFIX 80 cod. ZZEN07_0 Componente A (2,2 kg Resin) cod. ZZEN07_1 Componente B (8,2 kg Resin) cod. ZEN07 Componente C (9,6 kg Powder)	1,5 kg/m ² each mm of thickness	VASE + VASE kg 7,5	-	39073000
	CRYSTAL POOL SINGLE-COMPONENT, SATIN-EFFECT, ACRYLIC RESIN BASED, WATER-DISPERSED, SOLVENT-FREE PAINT AVAILABLE IN WHITE, SAND AND BLUE > Excellent water resistance even with chlorine and chemical agents > Suitable for contact with drinking water > Great resistance to UV radiation > Solvent-free				
	EQ16 CRYSTAL POOL WITHE ○				
EQ17	CRYSTAL POOL SAND ●	0,32 - 0,40 ℓ/m ²	4 ℓ VASE	-	32099000
EQ18	CRYSTAL POOL BLUE ●				
EQ11	CRYSTAL POOL WITHE ○				
EQ12	CRYSTAL POOL SAND ●	0,32 - 0,40 ℓ/m ²	14 ℓ VASE	-	32099000
EQ13	CRYSTAL POOL BLUE ●				
EQ14	CRYSTAL POOL (color group A) MINIMUM SUPPLY 28 ℓ	0,32 - 0,40 ℓ/m ²	14 ℓ VASE	-	32099000
EQ15	CRYSTAL POOL (color group B) MINIMUM SUPPLY 28 ℓ				
	CRYSTAL ONE-COMPONENT, TRANSPARENT, OPAQUE, ACRYLIC RESIN BASED, SOLVENT-FREE PAINT > Stable under UV rays and resistant to yellowing > Reduces absorption of water, oil and liquids in general > Colourless (darkening in the surface might occur) > Improves wear resistance				
	EQ19 CRYSTAL - 3 ℓ	0,30 - 0,34 ℓ/m ²	3 ℓ VASO	-	32099000
EQ20	CRYSTAL - 14 ℓ		14 ℓ VASO		

NOTES

JOINTS AND SEALANTS



JOINTS AND SEALANTS



**Joint covers - Profiles
Reinforcement Meshes**

pg. 24



**Waterstop
Hydro-expanding Mastics**

pg. 21



**Adhesives - Anchors
Mastics**




pg. 27





It's a waterproof life.



Waterstop - Hydro-expanding mastics



CODE	PRODUCT DESCRIPTION	PACKAGING	M/BOX	M/PALLET	HS CODE
	WT CONSTRUCTION EPDM HYDRO-SWELLABLE WATERSTOP REINFORCED WITH STEEL MESH				
	<ul style="list-style-type: none"> > High resistance to hydraulic load > High hydro-expansive stability and crack sealing capacity > Excellent adherence to the surface > Easy and quick application by nailing 				
BF01	WT C 25.15 - size: 25x15 mm - lenght 7 m Complete with progressive nails fixing	BOX 3 ROLLS	21 m	1008	40059900

	WT EXPANSION EPDM HYDRO-SWELLABLE WATERSTOP FOR JOINTS				
	<ul style="list-style-type: none"> > Perfect seal of expansion joints > High resistance to hydraulic load > Easy adaptation to the size of the structure to be waterproofed in correspondence of the expansion joint 				
BG01	WT E 20.20 - size: 20x20 mm - lenght 5 m	BOX 3 ROLLS	15 m	-	40059900
BG02	WT E 30.30 - size: 30x30 mm - lenght 5 m	4 BARS	4,80 m	-	40059900




	WT PANEL EPDM HYDRO-SWELLABLE MODULAR WATERSTOP PANEL				
	<ul style="list-style-type: none"> > High hydro-expansive stability and capacity > Easy adaptation to the size of the structures to be waterproofed in correspondence of the expansion joint > Can be hot-welded, glued, cut and adapted to the structure > Perfect seal of expansion joints and transit elements 				
GE01	WT P 25.120 - size: cm 120x25 - with mm 5	10 PANELS	12 M	360	40059100

CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	M/PALLET	HS CODE
	WT 102 HYDRO-EXPANDING BENTONITE-BASED PROFILE, RED COLOUR COMPLETE WITH RE.VO FIXING NET + PROGRESSIVE NAILS				
	<ul style="list-style-type: none"> > High resistance to hydraulic load > Easy and quick application > Excellent stability and adherence to the surface > High resistance to hydraulic load 				
BD03	ML 10 size: 25x20 mm - lenght 5 m (2-roll-box + 10 m RE.VO + nails)	BOX 2 ROLLS	10 m	320	40059900
BD02	ML 30 size: 25x20 mm - lenght 5 m (6-roll-box + 30 m RE.VO + nails)	BOX 6 ROLLS	30 m	720	40059900
BB00	 RE.VO NET Fixing yellow polypropilene net + nails	BOX	30 m	50	39023000

CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	PIECES/BOX	HS CODE
	BREAK SELF-SEALING WATERTIGHT BOX ELEMENT DESIGNED TO CONTROL AND SEAL ANY SPONTANEOUS CRACKS THAT DEVELOP IN THE REINFORCED CONCRETE.				
	<ul style="list-style-type: none"> > Perfect hydraulic water-tightness > Maximum control of shrinkage of reinforced concrete > Possibility of preparing continuous concrete castings without joints > Allows the reinforcement bars to be laid without interruptions 				
BC07	size: 18,5x100 cm - thickness 2 cm	BOX	10 m	10	40059900




Waterstop - Hydro-expanding mastics






CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	cc/PACK	HS CODE
GB12	 AKTI-VO 201 SYNTHETIC RUBBER HYDRO-EXPANDING MASTIC > Resolutive intervention on existing structures > Also applicable on wet and very uneven surfaces > It can support significant loads of water > Practical and fast for accurate applications				
	AKTI-VO 201	BOX	6 PCS.	320	32141010
AC044	 AKTI-VO BS MASTIC COMPOSED OF NATURAL SODIUM BENTONITE AND BUTYL RUBBER > Chemically stable , not affected by exposure to air or contact with sea water or contaminants > Also applicable on damp and very uneven surfaces > Allows for applications with variable thickness > Practical and fast for accurate applications				
	AKTI-VO BS	BOX	10 PCS.	600	3214101000
AC045	 AKTI-VO BS MASTIC COMPOSED OF NATURAL SODIUM BENTONITE AND BUTYL RUBBER > Chemically stable , not affected by exposure to air or contact with sea water or contaminants > Also applicable on damp and very uneven surfaces > Allows for applications with variable thickness > Practical and fast for accurate applications				
	AKTI-VO BS	PAIL	20 kg	-	3214101000

Waterstop - Hydro-expanding mastics







CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	-	HS CODE
	VOL-TEC RECTILINEAR ELEMENTS EXPANDING PROFILE FOR WIDE EXPANSION JOINTS > The pressure of the rubber structure can be adjusted manually , with torque adjustment possible after application > Easy testing and inspection of the state of efficiency of the profile > Quick and safe installation , thanks to the complete kit of required elements and preparation of the area > The whole guarantees constant pressure between the two parts of the structure, also in case of movement				
	GD01 size: L 290 x H 100 mm - thickness 50 mm	BOX	3 PCS.	-	40169300
	VOL-TEC CORNER ELEMENT EXPANDING PROFILE FOR WIDE EXPANSION JOINTS > The pressure of the rubber structure can be adjusted manually , with torque adjustment possible after application > Easy testing and inspection of the state of efficiency of the profile > Quick and safe installation , thanks to the complete kit of required elements and preparation of the area > The whole guarantees constant pressure between the two parts of the structure, also in case of movement				
	GD02 size: 170 x 170 x H 100 mm - thickness 50 mm	BOX	1 PC.	-	40169300
	VOL-TEC - NO STANDARD NO STANDARD PIECE - EXPANDING PROFILE FOR WIDE EXPANSION JOINTS > The pressure of the rubber structure can be adjusted manually , with torque adjustment possible after application > Easy testing and inspection of the state of efficiency of the profile > Quick and safe installation , thanks to the complete kit of required elements and preparation of the area > The whole guarantees constant pressure between the two parts of the structure, also in case of movement				
	GD04 VOL-TEC - NO STANDARD	-	1 PC.	-	40169300




Accessories

CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	-	HS CODE
GC12 	ULTRABOND POLIMER-BASED ADHESIVE MASTIC TO INSTALL/FIX ADEKA PROFILES 0,34 kg can with installation brush	CAN	0,34 kg	-	35069100
	GD03 	ROLL	25 m	-	39169010
	VOL-TEC DIMA PRE-CAST GUIDE				
	GD05 STANDARD size: thickness 50 mm - length 1 m	BOX	1 PC.	-	48115900
GD06	PER STRING size: thickness 55 mm - length 1 m	BOX	1 PC.	-	48115900








CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	WIDTH/cm	HS CODE
 BI FLEX SYSTEM TPE POLYMER-BASED ELASTIC BAND > 100% waterproof with positive/negative hydrostatic pressure > Control over hydraulic water-tightness , which is visible and repairable > High elongation capacity and absorption of dilatation > Excellent adhesion on different substrates, such as concrete, mortar, stone, steel and galvanised steel					
EW05	BI FLEX - H 20 size: 0,5 mm	BOX	40 m	10	39204910
EW02	BI FLEX - H 10 size: 1,0 mm	BOX	20 m	10	39204910
EW01	BI FLEX - H 20 size: 1,0 mm	BOX	20 m	20	39204910
EW04	BI FLEX - H 20 size: 1,5 mm	BOX	15 m	20	39204910
 GARVO due JOINT COVER STRIP REINFORCED WITH THERMO-PLASTIC RUBBER					
EE01		BOX	25 m	8,5	63079098
 GARVO 3 JOINT COVER STRIP REINFORCED WITH RUBBER > Easy and quick application > Extremely waterproof > High elongation capacity > Excellent adhesion					
ED142		BOX	20 m	10	39219090
 GARVO 5 JOINT COVER STRIP REINFORCED WITH RUBBER > Easy and quick application > Extremely waterproof > High elongation capacity > Excellent adhesion					
ED141		BOX	20 m	15	39219090
 AQUASCUD JOIN ELASTICIZED JOINT COVER BAND > Application is practical and simple, easy and quick thanks to the self-adhering capacity > Good impermeability > Good elasticity > Good adhesion on different types of surfaces					
CD01		BOX	25 m	10 cm	39219090
 AQUASCUD JOIN BT ELASTICIZED JOINT COVER BAND WITH ADHESIVE BUTYL RUBBER > Application is practical and simple, easy and quick thanks to the self-adhering capacity > Good impermeability > Good elasticity > Good adhesion on different types of surfaces					
CD04		BOX	20 m	10 cm	56031410



CODE	PRODUCT DESCRIPTION	PACKAGING	WIDTH	LENGHT	HS CODE
	XNET MULTIDIRECTIONAL SYNTHETIC COMPOSITE ELASTICIZED NET > Resistant to alkaline environment > Quick installation thanks to its considerable capacity to be permeated > Increases the crack bridging ability and fatigue strength of the polymer-modified sheaths and mineral levelling compounds > It does not alter the breathability characteristics of the mixture in which it is combined				
	ET07 H.16 size: 50x0,16 m	ROLL	16 cm	50 m	56031290
	ET06 H.33 size: 50x0,33 m	ROLL	33 cm	50 m	56031290
	ET05 H.100 size: 50x1 m	ROLL	100 cm	50 m	56031290
	FLEXONET ELASTIC POLYPROPYLENE REINFORCING NET > Snag resistant and resistant to alkaline environment > Easy installation thanks to its considerable capacity to be permeated > Improves the crack bridging ability and all mechanical properties of PLASTIVO/CP1 products > It does not alter the breathability characteristics of the mixture that it is added to				
	ET03 H.16 size: 50x0,16 m	ROLL	16 cm	50 m	60053500
	ET02 H.33 size: 50x0,33 m	ROLL	33 cm	50 m	60053500
	ET01 H.100 size: 50x1 m	ROLL	100 cm	50 m	60053500
	REVOMAT H.100 FIBERGLASS MESH 40x40mm ALKALI RESISTANT > Good flexibility to facilitate shaping for changes in direction > Excellent durability , unalterable in damp and chemically aggressive environments > High tensile strength (approximately 3 times greater than steel) > It features a special anti-alkaline surface treatment (finis which enhances the properties and provides dimensional stability)				
	BE00 REVOMAT H. 100	ROLL	100 cm	30 m	70196600


Accessories

CODE	PRODUCT DESCRIPTION		PACKAGING	CONTENT	DIMENSION	HS CODE
EU01		SUPERBOND ADHESIVE MASTIC FOR BONDING OF RUBBER GASKETS ON CONCRETE AND JUNCTION OF JOINT COVERING BANDS 0,34 kg can + brush dispenser	CAN	0,34 kg	-	35069100
	AQUASCUD JOIN BT ANGULAR PRE-SHAPED BAND COVER, WITH ADHESIVE BUTYL RUBBER					
CD05		ANGULAR 90°	BOX	10 PCS.	12x12 cm	56031410
CD06		ANGULAR 270°			10,5x10,5 cm	
	GARVO ANGULAR FELT-COATED RUBBER					
ED144		ANGULAR 90°	BOX	10 PCS.	12x12 cm	39219090
ED145		ANGULAR 270°			12x12 cm	



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
EY02	BI BOND EPOXY ADHESIVE FOR BONDING BI-FLEX > 100% waterproof with positive/negative hydrostatic pressure > Control over hydraulic water-tightness , which is visible and repairable > High elongation capacity and absorption of dilatation > Excellent adhesion on different substrates, such as concrete, mortar, stone, steel and galvanised steel	1,5÷1,6 kg/m ² per mm thickness	5 kg VASE + VASE	500 + 500	39073000
		0,6 kg/m BI FLEX H.10 1,0 kg/m BI FLEX H.20	10 kg VASE + VASE	500 + 500	39073000
EY01	10 KG (Component A kg 5 + Component B kg 5) cod. EY12 Component A - cod. EY13 Component B				
CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	cc/PACK	HS CODE
RB11	BI MASTIC DEFORMABLE ADHESIVE MASTIC WITH HIGH PERFORMANCE > High thixotropy , adhesion and durability, and U.resistance > Hygroscopic behaviour , cross-linked with environmental humidity > Also applicable on damp surfaces > Applicable on a wide range of surfaces , both absorbent and non-absorbent	BOX	10 PCS.	600	32149000
FN01	BI FIX 300 AMPHIBIO TWO-COMPONENT CHEMICAL ANCHOR > Fast, solid and resolutive anchoring > It can be fastened on horizontal, vertical, inclined or overhead axis > Also suitable for fixing on intact or cracked concrete supports, solid and perforated masonry, stone, wood > Applicable on dry, wet or flooded concrete CE EAD 330499-01-0601 ETA-20/0352	BOX	2 PCS.	600	32141010
FN03	CARBON STEEL CONNECTOR CARBON STEEL CONNECTOR WITH ELECTROLYTIC GALVANIZING > Solid anchoring thanks to double disc > Allows for the absence of reinforcement mesh in combination with thin fibre-reinforced mortars. In the presence of metal meshes, it does not require fixing to them > Quick and easy application thanks to the installation guide disc		1 PC.	-	73160000
FN02	CONNECTOR 38 size: 185 mm (38 + 147 mm)		1 PC.	-	73160000




CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
	 <p>REPOSOL TWO-COMPONENT EPOXY RESIN FOR BONDING AND IMPREGNATION</p> <ul style="list-style-type: none"> > Simple application > Versatility > High performance 				
HI007	<p>5 KG (Component A 5 kg + Component B 3 kg) cod. H003 Component A cod. H004 Component B</p>	–	8 kg VASE + VASE	–	39073000

DAMP-PROOF RENOVATION



DAMP-PROOF RENOVATION



pg. 31





Damp-proof restoration systems



It's a waterproof life.

Damp-proof restoration systems




CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	KG/PALLET	HS CODE
	CALIBRO RINZAFFO READY-MIX SALT-PROOF RENDER > Suitable to coat all types of walls > It guarantees long-lasting sound and stable restoration > It inhibits the development of any form of condensation > Also machine-applicable				
		6~6,5 kg/m ² each 0,5 cm of thickness	BAG kg 25	1200	38245090
	CALIBRO P.E. INTONACO READY-MIX PLASTER, DAMP-PROOF, SALT-PROOF, CONDENSATION-PROOF > Suitable to coat all types of walls > It guarantees long-lasting sound and stable restoration > It inhibits the development of any form of condensation > Also machine-applicable CE UNI EN 998-1				
		9~9,5 kg/m ² each cm of thickness	BAG kg 20	1200	38245090
	CALIBRO NHL READY-MIX PLASTER WITH NATURAL HYDRAULIC LIME 3.5 DAMP-PROOF, SALT-PROOF, CONDENSATION-PROOF > Natural lime-based product , NHL according to EN 459 > Eco compatible > 2 in 1 : Rinzafo and Intonaco in a single solution > Also machine-applicable CE UNI EN 998-1 EPD 0298				
		10,5~11 kg/m ² each cm of thickness	BAG kg 20	1200	38245090
	X-LIME LIME-BASED PLASTER FINISHING, WHITE COLOUR > High breathability > Easy workability on existing and newly-built surfaces > Excellent finish results , even in the presence of micro-cracks and old paint > Compatibility with old walls				
		1,4 kg/m ² each mm of thickness	BAG kg 20	1200	38245090

Damp-proof restoration systems



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	-	HS CODE
	TRIPLEZERO SUPER-HYDROPHOBIC ANTI-HUMIDITY CREAMY EMULSION FOR INJECTION. > Ready to use and easy application for injection > Suitable for both indoor and outdoor application > Effective and long-lasting water resistant protection > Odourless and solvent-free				
					
HL001	TRIPLEZERO	10 cc x 1 cm of wall thickness x 1 m of wall lenght	BOX 10 PCS.	cc 600/PACK	39100000
HL004	TRIPLEZERO 15 kg	10 cc x 1 cm of wall thickness x 1 m of wall lenght	VASE kg 15	-	39100000

CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
	TRIPLEZERO - T SUPERHYDROPHOBIC DAMP-PROOFING CREAMY EMULSION APPLICABLE BY ROLLER/BRUSH/AIRLESS > Suitable for both indoor and outdoor application > Effective and long-lasting transparent protection > Excellent resistance against ageing agents such as UV rays, un/ freezing, marine aerosol				
HL002	TRIPLEZERO T 5 kg	100~400 g/m²	VASE kg 5	-	39100000
HL005	TRIPLEZERO T 15 kg	100~400 g/m²	VASE kg 15	-	39100000

RECOVERY AND PROTECTION



RECOVERY AND PROTECTION



pg. 35

Repair Mortars







pg. 37

**Waterproof levelling compounds
- Primers - Paints**



It's a waterproof life.







CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
	SANOFE POLYMERS AND CEMENT-BASED PROTECTIVE COATING FOR ARMOR IRONS > Also effective on rust-corroded rods > Excellent grip for future repair mortars > Easy and quick application > Use directly on exposed steel bars CE UNI EN 1504-7				
	FB25	30 g/m bars \varnothing 8 mm 60 g/m bars \varnothing 16 mm	VASE 1 kg	150	38245090
	FIBROeRASO SEMI-RAPID THIXOTROPIC MORTAR WITH MEDIUM MODULUS ELASTICITY AND CONTROLLED SHRINKAGE > High impermeability > Easy workability and rapid application > High resistance to carbonation > Excellent adhesion to concrete and reinforcement bars CE UNI EN 1504-3 CC R4 CE UNI EN 1504-2 PRINCIPI MC e IR				
	FA264	17,5 kg/m ² for each cm of thickness	BAG 20 kg	1200	38245090
	FIBROMIX 40 CEMENT-BASED READY-MIX, FIBRE-REINFORCED, MEDIUM ELASTIC MODULE > High impermeability > Good resistance against the aggression of atmospheric chemical agents > Excellent adhesion to concrete and reinforcement bars > Light colour CE UNI EN 1504-3 CC R4				
	FA262	18 kg/m ² for each cm of thickness	BAG 25 kg	1200	38245090
	FIBRO HFR THREE-COMPONENT FLOWABLE REPAIR MORTAR REINFORCED WITH STEEL FIBERS > The presence of the steel fibre gives it its firm behaviour > Applicable in thicknesses between 1 and 10 cm > Total resistance to carbonation phenomena > Very high mechanical compression and flexural strength CE UNI EN 1504-3 CC R4 EPD 0298				
	FI03	FIBRO HFR - COMPONENT A - POWDER	BAG 25 kg	1200	38245090
FI04	FIBRO HFR - COMPONENT B - LIQUID	25 kg (A + B + C) per cm thickness	PAIL 14 kg	616	2909430000
FI05	STEEL FIBERS - COMPONENT C - STEELS		BOX 5 kg	-	83089000




MIXING RATIO 100 KG POWDER + 14 kg LIQUID + 5 kg FIBERS

Repair Mortars



CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	kg/PALLET	HS CODE
FF26	 FLEXOMIX 30 CEMENT-BASED READY-MIX, LOW ELASTIC MODULE > High impermeability > Good resistance against the aggression of atmospheric chemical agents > Low modulus of elasticity that is capable of following the movements of the structure > Excellent thixotropy that allows the product to be applied without formwork  UNI EN 1504-3 PCC R3	16 kg/m ² for each cm of thickness	BAG kg 25	1200	38245090
FE26	 FLOWMIX 70 CEMENT-BASED READY-MIX, SELF-LEVELLING, POURABLE, HIGH ELASTIC MODULE > Waterproof > High mechanical resistance > Good levelling properties > High resistance anchorings  UNI EN 1504-3 CC R4	19 kg/m ² for each cm of thickness	BAG kg 25	1200	38245090


Accessories


CODE	PRODUCT DESCRIPTION	PACKAGING	CONTENT	DIMENSION	HS CODE
FN03	 CARBON STEEL CONNECTOR CARBON STEEL CONNECTOR WITH ELECTROLYTIC GALVANIZING		1 PC.	-	73160000
	CONNECTOR 20 size: 80 mm (20 + 60 mm)				
FN02	CONNECTOR 38 size: 185 mm (38 + 147 mm)		1 PC.	-	73160000
FN01	 BI FIX 300 AMPHIBIO TWO-COMPONENT CHEMICAL ANCHOR  EAD 330499-01-0601 ETA-20/0352	BOX	2 PCS.	600 ml	32141010

Waterproof levelling compounds - Primers - Paints







CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	GRANULOMETRY	kg/PALLET	HS CODE
	CPØ ACRYL-SILOSSANIC READY-TO-USE PIGMENTED COATING HIGHLY BREATHABLE, ELASTIC AND WATER-REPELLENT FOR INDOOR AND OUTDOOR USE > Fine aesthetic appearance , available in different sizes > Compact effect, excellent filling and covering capability > Resistant to the formation and proliferation of mould, algae and fungi > Long-lasting thanks to high resistance to atmospheric agents and UV rays CE UNI EN 15824				
	0,4 mm				
ER05A	CPØ (color group A)	1,6 - 1,8 kg/m ²	0,4 mm	25 kg VASE	32099000
ER05B	CPØ (color group B)				
	1,0 mm				
	CPØ (color group A)	1,8 - 2 kg/m ²	1,0 mm	25 kg VASE	32099000
ER03B	CPØ (color group B)				
	1,2 mm				
	CPØ (color group A)	2 - 2,2 kg/m ²	1,2 mm	25 kg VASE	32099000
ER02B	CPØ (color group B)				
	1,5 mm				
	CPØ (color group A)	2,2 - 2,5 kg/m ²	1,5 mm	25 kg VASE	32099000
ER04B	CPØ (color group B)				

CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	GRANULOMETRY	kg/PALLET	HS CODE
	CP1 WATERPROOFING, ELASTIC, HIGHLY BREATHABLE MINERAL COATING TWO-COMPONENT IN WHITE COLOUR > Breathability and elasticity all in one solution > Extremely effective anti-carbonation barrier to protect the concrete > High protection that extends the service life of the structure > Resistant to the formation and proliferation of fungi, algae and mould CE UNI EN 1504-2 PRINCIPI PI, MC e IR EPD 0298				
	ER01 (15 KG POWDER + 5,7 KG LIQUID) cod. ZR001 15 kg powder cod. ZZZR1 5,7 kg liquid	2,5 kg output a thickness of 2 mm/m ²	BAG + PAIL 20,7 kg	1656	38245090





	X-LIME LIME-BASED PLASTER FINISHING, WHITE COLOUR > High breathability > Easy workability on existing and newly-built surfaces > Excellent finish results , even in the presence of micro-cracks and old paint > Compatibility with old walls				
	FM001 X-LIME	1,4 kg/m ² for each mm thickness	BAG 20 kg	1200	38245090

Waterproof levelling compounds - Primers - Paints





CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	-	HS CODE
	TRIPLEZERO - T SUPERHYDROPHOBIC DAMP-PROOFING CREAMY EMULSION APPLICABLE BY ROLLER/BRUSH/AIRLESS > Suitable for both indoor and outdoor application > Effective and long-lasting transparent protection > Excellent resistance against ageing agents such as UV rays, unfreezing, marine aerosol				
	HL002 TRIPLEZERO T 5 Kg	100~400 g/m ²	VASE kg 5	-	39100000
HL005	TRIPLEZERO T 15 kg	100~400 g/m ²	VASE kg 15	-	39100000
	PROCLEAN DISINFECTANT AND ANTIMYCOTIC TREATMENT > It disinfects contaminated surfaces > It does not require dilution with water > Not film-forming > Can be applied in closed and poorly ventilated environments as it is solvent-free				
	EC254 PROCLEAN 5 l	0,15 l/m ²	CAN 5 l	-	39069090
EC255	PROCLEAN 20 l		CAN 20 l	-	39069090
	PROFIX 20 POLI-SILOSSANIC AND ACRYLIC PRIMING TREATMENT TO CONSOLIDATE AND REGULARIZE THE ABSORPTION OF SUBSTRATES, MOSTLY CONCRETE-BASED > To strengthen the surface , preventing the formation of a superficial film > Removes dust from mineral surfaces > Increases the adhesion of levelling compounds, coatings or finishes in general > Can be applied in closed and poorly ventilated environments as it is odourless and solvent-free				
	EC253 PROFIX 20 5 l	0,2÷0,3 l/m ²	CAN 5 l	-	39069090
	PROFIX 30 PRIMING TREATMENT TO INCREASE ADHESION PERFORMANCES ON CONCRETE SUBSTRATES > High penetrating power and effective strengthening effect , even with low-porous surfaces > Removes dust from mineral surfaces > It increases adhesion of coatings, finishes and waterproofing products to the surface > Can be applied in closed and poorly ventilated environments as it is odourless and solvent-free				
	EN01 PROFIX 30 5 l	0,2÷0,3 l/m ²	CAN 5 l	-	39069090
EN02	PROFIX 30 25 l		CAN 25 l	-	39069090




















CODE	PRODUCT DESCRIPTION	CONSUMPTION OUTPUT	PACKAGING CONTENT	-	HS CODE
	<p>PROFIX 40 COLOURED PRIMER FOR CP0 CONSUMPTION, TO INCREASE ADHESION PERFORMANCES ON CONCRETE SUBSTRATES</p> <ul style="list-style-type: none">> Good water resistance and vapour permeability> Good coating capacity> It increases the adhesion of CP0, PAINT AIR and PAINT PROTECTION> Can be applied in closed and poorly ventilated environments as it is solvent-free				
5 LITERS					
EN05	PROFIX 40 (colors group A)		VASE 5 ℓ	-	39069090
EN06	PROFIX 40 (colors group B)	0,15÷0,3 ℓ/m²			
14 LITERS					
EN03	PROFIX 40 (colors group A)		VASE 14 ℓ	-	39069090
EN04	PROFIX 40 (colors group B)				
	<p>PAINT AIR ACRYL-SILOSSANIC PAINT, HIGHLY PERMEABLE TO VAPOUR, WATER-REPELLENT, DEFORMABLE, RESISTANT TO ATMOSPHERIC AGENTS</p> <ul style="list-style-type: none">> Excellent water repellency> Excellent resistance against aggressive physical and chemical atmospheric agents (ex: wind, smog, etc)> Highly resistant to UV rays> Vast range of colours available				
ES01A	PAINT AIR (color group A)	0,3 ℓ/m²	VASE 14 ℓ	-	32091000
ES01B	PAINT AIR (color group B)			-	32091000
	<p>PAINT PROTECTION WATERPROOF STYROL-ACRYLIC PAINT, RESISTANT TO ATMOSPHERIC AGENTS, ANTI-CARBONATION AND EXCELLENT PERMEABILITY TO VAPOUR</p> <ul style="list-style-type: none">> Extremely effective anti-carbonation barrier to protect the concrete> Excellent resistance against aggressive physical and chemical atmospheric agents (ex: wind, smog, etc)> Highly resistant to UV rays> Vast range of colours available				
 UNI EN 1504-2 PRINCIPI PI, MC e IR					
EG24A	PAINT PROTECTION (color group A)	0,4 ℓ/m²	VASE 14 ℓ	-	32091000
EG24B	PAINT PROTECTION (color group B)			-	32091000

Accessories

CODE	PRODUCT DESCRIPTION	PACKAGING	WIDTH	LENGHT	HS CODE
ET07	 XNET MULTIDIRECTIONAL SYNTHETIC COMPOSITE ELASTICIZED NET	ROLL	16 cm	50 m	56031290
ET06	H.16 size: 50x0,16 m	ROLL	16 cm	50 m	56031290
ET05	H.33 size: 50x0,33 m	ROLL	33 cm	50 m	56031290
ET04	H.100 size: 50x1 m	ROLL	100 cm	50 m	56031290
ET03	 FLEXONET ELASTIC POLYPROPYLENE REINFORCING NET	ROLL	16 cm	50 m	60053500
ET02	H.16 size: 50x0,16 m	ROLL	16 cm	50 m	60053500
ET01	H.33 size: 50x0,33 m	ROLL	33 cm	50 m	60053500
ET00	H.100 size: 50x1 m	ROLL	100 cm	50 m	60053500

Work tools

CODE	PRODUCT DESCRIPTION		CONTENT	HS CODE	
HGII3		BRUSH	SINGLE PIECE	82055910	
HGII10		SPIKE ROLLER - 7 kg FOR THE APPLICATION OF AQUASCUD BASIC, PROVIDED WITHOUT WOOD HANDLE	SINGLE PIECE	960340900	
HGII6		SPIKE ROLLER - REPLACEMENT	SINGLE PIECE	82055910	
HGII15		SERRATED METAL SQUEEGEE PROVIDED WITHOUT WOOD HANDLE	SINGLE PIECE	82055910	
HGII16		SERRATED TROWEL 3,5 mm FOR THE APPLICATION OF AQUASCUD	SINGLE PIECE	82055910	
HGII17		ROUND TROWEL FOR THE APPLICATION OF CP, X-RAPID, X-LIME, AQUASCUD	SINGLE PIECE	82055910	
HGII18		SERRATED TROWEL 2 mm FOR THE APPLICATION OF AQUASCUD 500	SINGLE PIECE	82055910	
EP01		PLASTIVO ROLLER PROVIDED WITHOUT WOOD HANDLE	SINGLE PIECE	960340900	
EP02		PLASTIVO ROLLER - REPLACEMENT	SINGLE PIECE	960340900	
HGII5		WOOD HANDLE	SINGLE PIECE	82055910	
CODE	PRODUCT DESCRIPTION		PACKAGING	CONTENT	HS CODE
HL003		UNIPACK GUN MANUAL SAELING GUN FOR UNIPACK	-	SINGLE PIECE	82055980
HL008		AKTI-VO BS KIT	BAG	5 PCS.	82055980
HL009		KIT MIXER FOR BI FIX AND TRIPLEZERO	BAG	3 PCS.	82055980
HL010		BI MASTIC KIT	BAG	5 PCS.	82055980
HL011		SPOUT HOLDER FOR UNIPACK	-	SINGLE PIECE	82055980
HL012		GASKET SPOUT HOLDER FOR UNIPACK	-	SINGLE PIECE	82055980
HL013		NOZZLE HOLDER FOR UNIPACK	-	SINGLE PIECE	82055980

The company

Established in 1976, after forty-five years of activity, **Volteco** is today a provider of waterproofing solutions for the construction industry. **Volteco** works with passion and commitment on both national and international fields, for companies, through a network of distributors and applicators, cooperating with designers. Choosing **Volteco** means preventing, or solving, the problems caused by water.


Volteco solutions are in fact designed to meet specific needs based on different field of applications:

- Waterproofing of basements;
- Waterproofing of pools and tanks;
- Waterproofing of terraces and flat roofs;
- Treatment of damp walls;
- Facade restoration.

Thanks to a complete service consisting in technical expertise, professional approach and a trained and constantly updated installation network, **Volteco** offers personalized advice at every stage of the construction process. **Volteco** is a specialist in his field, the Specialist of Waterproofing!



WHAT CAN WE OFFER?



PREMIUM
WATERPROOFING
PRODUCTS



MORE THAN
2200
CASE HISTORIES



PROJECTS IN
MORE THAN
40 COUNTRIES



MORE THAN
300
QUALIFIED INSTALLERS

Volteco's Services *at your disposal*

-
- > **Services for the designer**




-
- > **Support for professionals and installers**



-
- > **Qualified installers**



-
- References:**
 - > **www.volteco.com**





It's a waterproof life.



COMPANY CERTIFIED MANAGEMENT SYSTEM QUALITY
ISO 9001 - ENVIRONMENT ISO 14001 - SAFETY ISO 45001



VOLTECO
WATERPROOF TECHNOLOGY

VOLTECO S.p.A.
Via delle Industrie, 47
31050 Ponzano Veneto (TV) Italy
Tel. +39 0422 9663 Fax +39 0422 966401
volteco@volteco.it - www.volteco.com

The information, images and text found in this illustrative brochure are the property of Volteco spa; they are purely indicative and subject to change at any time without prior notice. The updated version of this documentation is found on www.volteco.com.

AT | D | 02 | 00 | - 07 / 2023 | EN