

# WT PANEL

Supply and installation of modular waterstop panel based on AMPHIBIA copolymer in hydro-expansive EPDM.

The product must be used for:

- Waterproofing of expansion and contraction joints of underground reinforced concrete structures in combination with the WT EXPANSION hydro-expansive profile and synthetic profiles in general
- Reinforced concrete slab head waterproofing against provisional structures
- Extrados sealing of horizontal or vertical concrete construction joints
- Sealing of discontinuous elements between adjoining concrete and/or steel surfaces

The material must have the following characteristics:

Specification	Declared performance
<b>WT P 250</b>	-
<i>Dimension</i>	250 mm x 10 m ( $\pm 10\%$ )
<i>Thickness</i>	5 mm
<i>Weight</i>	14,0 $\pm$ 0,7 kg
<i>Volumetric expansion (7 days)</i>	200%
<b>WT P 125</b>	-
<i>Dimension</i>	125 mm x 1,2 m ( $\pm 10\%$ )
<i>Thickness</i>	5 mm
<i>Weight</i>	0,8 $\pm$ 0,04 kg
<i>Volumetric expansion (7 days)</i>	200 %

as well as Wt Panel Volteco or a product with equal or superior characteristics

The technical data must be supported by test certification issued by an accredited official laboratory and / or be subjected to quality control according to ISO 9001.

For further details on the individual products and installation specifications, refer to the relevant technical data sheets which can be downloaded in the updated version on the website [www.volteco.com](http://www.volteco.com).