

WT STRIP

Supply and installation of waterstop tape based on Amphibia copolymer in hydro-expansive EPDM, capable of sealing contact surfaces by pressure when water passes through.

Thanks to its flexibility, it can also be applied to particularly articulated products or uneven surfaces.

The product must be used for:

- Sealing of penetrations, concrete, metal and plastic pipes embedded in reinforced concrete
- Joint sealing of pipes, ducts, gullies, tanks, boxes and prefabricated concrete, fibre concrete or steel ditches
- To make gaskets between precast elements
- Internal sealing of discontinuous elements between contiguous concrete and/or steel surfaces

The material must have the following characteristics:

Specification	Values
<i>Dimension</i>	30x5 mm ($\pm 10\%$) 50x5 mm ($\pm 10\%$)
<i>Thickness</i>	5 mm
<i>Roll weight 30x5 mm</i>	3,0 Kg $\pm 0,15$ kg
<i>Roll weight 50x5 mm</i>	4,0 Kg $\pm 0,20$ kg
<i>Volumetric expansion (7 days)</i>	200%

as well as Wt Strip System Volteco or a product with equal or superior characteristics.

The technical data must be supported by test certification issued by an accredited official laboratory and / or be subjected to quality control according to ISO 9001.

For further details on the individual products and installation specifications, refer to the relevant technical data sheets which can be downloaded in the updated version on the website www.volteco.com.