

AQUASCUD JOIN BT

Supply and installation of self-adhesive waterproofing tape to be used in combination with PLASTIVO or AQUASCUD polymer-modified mineral coatings.

The tape must consist of a non-woven alkali-resistant polypropylene fabric coupled with a layer of butyl adhesive protected by a removable pre-cut silicone film paper.

The product must be used for:

- Waterproofing of the wall/floor connection point of terraces and balconies or of the connection between surfaces subject to thermal or dynamic movements
- To seal joints between different materials (cement-based screed, metal, ceramic, fittings and drains, etc)
- To seal connections with poor access, such as thresholds/screed

The material must have the following characteristics:

Specification	Values
Colour	white/grey
Roll width	100 mm
Roll width	20 m
Total thickness	0.8 mm
Tensile strength	> 15 N/15 mm
Elongation at maximum load	> 35%
Application temperature (min-max °C)	+5°C +30°C
Working temperature (min-max °C)	-30°C +60°C

as well as Aquascud Join Bt Volteco or a product with equal or superior characteristics.

The technical data must be supported by test certification issued by an accredited official laboratory and / or be subjected to quality control according to ISO 9001.

For further details on the individual products and installation specifications, refer to the relevant technical data sheets which can be downloaded in the updated version on the website www.volteco.com.