

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Code: ER05
Product name: CP0

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Continuous plastic coating for exteriors and interiors with silicone additives

1.3. Details of the supplier of the safety data sheet

Name: VOLTECO S.P.A
Full address: via delle industrie 47
District and Country: 31050 Ponzano Veneto (TV)
Italia
Tel.: 04229663
e-mail address of the competent person responsible for the Safety Data Sheet: volteco@volteco.it

1.4. Emergency telephone number

For urgent inquiries refer to:
European emergency phone number 112
Volteco - +39-0422-9663
Ireland
Poison information centre: 01 809 2166 (Daily 8am-10pm) In case of emergency call 999 or 112
Malta
In case of emergency call: +356 2395 2000 (24h)

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

Hazardous to the aquatic environment, chronic toxicity, category 3 H412 Harmful to aquatic life with long lasting effects.

2.2. Label elements

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms: --

Signal word: --

Hazard statements:

H412 Harmful to aquatic life with long lasting effects.
EUH208 Contains: REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)
2-OCTYL-2H-ISOTHIAZOL-3-ONE
1,2-benzisothiazolin-3-one
May produce an allergic reaction.

Precautionary statements:

P501 Dispose of the product / container in accordance with current legislation.

VOLTECO S.P.A

ER05 - CP0

Revision nr.2
Dated 10/04/2026
Printed on 10/04/2026
Page n. 2 / 15
Replaced revision:1 (Dated 03/09/2025)

EN

SECTION 2. Hazards identification ... / >>

P102	Keep out of reach of children.
P101	If medical advice is needed, have product container or label at hand.
P273	Avoid release to the environment.

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration $\geq$ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification	x = Conc. %	Classification (EC) 1272/2008 (CLP)
ETHYLENE GLYCOL		
INDEX 603-027-00-1	0,7 ≤ x < 0,8	Acute Tox. 4 H302, STOT RE 2 H373 LD50 Oral: 500 mg/kg
EC 203-473-3		
CAS 107-21-1		
REACH Reg. 01-2119456816-28-XXXX		
2-(2-BUTOXYETHOXY)ETHANOL		
INDEX 603-096-00-8	0,2 ≤ x < 0,3	Eye Irrit. 2 H319
EC 203-961-6		
CAS 112-34-5		
REACH Reg. 01-2119475104-44-XXXX		
1,2-benzisothiazolin-3-one		
INDEX 613-088-00-6	0 < x < 0,1	Acute Tox. 2 H330, Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic Chronic 1 H410 M=1 ATE Oral: 500 mg/kg, LC50 Inhalation mists/powders: 0,21 mg/l
EC 220-120-9		
CAS 2634-33-5		
Diuron		
INDEX 006-015-00-9	0 < x < 0,025	Carc. 1B H350, STOT RE 2 H373, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10
EC 206-354-4		
CAS 330-54-1		
REACH Reg. 01-2119517622-45-XXXX		
Zinc pyrithione		
INDEX	0 < x < 0,1	Repr. 1B H360D, Acute Tox. 2 H330, Acute Tox. 3 H301, STOT RE 1 H372, Eye Dam. 1 H318, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=1 LD50 Oral: 300 mg/kg, LC50 Inhalation mists/powders: 0,14 mg/l
EC		
CAS		
2-OCTYL-2H-ISOTHIAZOL-3-ONE		
INDEX 613-112-00-5	0 < x < 0,0015	Acute Tox. 2 H330, Acute Tox. 3 H301, Acute Tox. 3 H311, Skin Corr. 1 H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=10, EUH071 Skin Sens. 1A H317: ≥ 0,0015% LD50 Oral: 125 mg/kg, LD50 Dermal: 311 mg/kg, ATE Inhalation mists/powders: 0,051 mg/l
EC 247-761-7		
CAS 26530-20-1		
REACH Reg. 01-2120768921-45-XXXX		
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)		
INDEX 613-167-00-5	0 < x < 0,0015	Acute Tox. 2 H310, Acute Tox. 2 H330, Acute Tox. 3 H301, Skin Corr. 1B H314, Eye Dam. 1 H318, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=100, Aquatic Chronic 1 H410 M=100, Classification note according to Annex VI to the CLP Regulation: B Skin Corr. 1 H314: ≥ 0,6%, Skin Irrit. 2 H315: ≥ 0,6% - < 0,6%, Skin Sens. 1A H317: ≥ 0,0015%, Eye Dam. 1 H318: ≥ 0,6%, Eye Irrit. 2 H319: ≥ 0,6% LD50 Oral: >50 mg/kg, LD50 Dermal: >50 mg/kg, LC50 Inhalation mists/powders: 0,31 mg/l/4h
EC		
CAS 55965-84-9		
REACH Reg. 01-2120764691-48-XXXX		

The full wording of hazard (H) phrases is given in section 16 of the sheet.

SECTION 4. First aid measures

4.1. Description of first aid measures

No effects requiring implementation of special first aid measures are expected. The following information represents practical indications of correct behaviour in the event of contact with a chemical product, even if not hazardous.

In case of doubt or in the presence of symptoms contact a doctor and show him this document.

In case of more severe symptoms, ask for immediate medical aid.

EYES: Remove, if present, contact lenses if the situation allows you to do so easily. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Take off contaminated clothing. Wash immediately and thoroughly with running water (and soap if possible). Get medical advice. Avoid further contact with contaminated clothing.

INGESTION: Do not induce vomiting unless explicitly authorised by a doctor. Do not give anything by mouth to an unconscious person. Get medical advice/attention.

INHALATION: Remove victim to fresh air, away from the accident scene. Get medical advice/attention.

Rescuer protection

It is good practice for rescuers lending support to a person who has been exposed to a chemical substance or to a mixture to wear personal protective equipment. The nature of such protection depends on the hazard level of the substance or mixture, on the type of exposure and on the extent of the contamination. In the absence of other more specific indications, use of disposable gloves in the event of possible contact with body fluids is recommended. For the type of PPE suitable for the characteristics of the substance or mixture, see section 8.

4.2. Most important symptoms and effects, both acute and delayed

Specific information on symptoms and effects caused by the product are unknown.

DELAYED EFFECTS: Based on the information currently available, there are no known cases of delayed effects following exposure to this product.

4.3. Indication of any immediate medical attention and special treatment needed

If symptoms occur, whether acute or delayed, consult a doctor.

Means to have available in the workplace for specific and immediate treatment

Running water for skin and eye wash.

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

UNSUITABLE EXTINGUISHING EQUIPMENT

None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE

Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent

VOLTECO S.P.A		Revision nr.2 Dated 10/04/2026 Printed on 10/04/2026 Page n. 4 / 15 Replaced revision:1 (Dated 03/09/2025)	EN
ER05 - CP0			
SECTION 6. Accidental release measures ... / >>			
any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.			
6.2. Environmental precautions			
The product must not penetrate into the sewer system or come into contact with surface water or ground water.			
6.3. Methods and material for containment and cleaning up			
Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material. Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.			
6.4. Reference to other sections			
Any information on personal protection and disposal is given in sections 8 and 13.			
SECTION 7. Handling and storage			
7.1. Precautions for safe handling			
Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.			
7.2. Conditions for safe storage, including any incompatibilities			
Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.			
7.3. Specific end use(s)			
Information not available			
SECTION 8. Exposure controls/personal protection			
8.1. Control parameters			
Regulatory references:			
ALB	Shqipëria	VENDIM Nr. 522, datë 6.8.2014 PËR MIRATIMIN E RREGULLORES “PËR MBROJTJEN E SIGURISË DHE SHËNETIT TË PUNËMARRËSVE NGA RISQET E LIDHURA ME AGJENTËT KIMIKË NË PUNË”	
DEU	Deutschland	WirkungDosisNOAELMAK-und BAT-Werte-Liste 2024 Ständige Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe	
ESP	España	Límites de exposición profesional para agentes químicos en España 2024	
FRA	France	Valeurs limites d'exposition professionnelle aux agents chimiques en FranceDécret n° 2021-1849 du 28 décembre 2021	
HRV	Hrvatska	PRAVILNIK O IZMJENAMA I DOPUNAMA PRAVILNIKA O ZAŠTITI RADNIKA OD IZLOŽENOSTI OPASNIM KEMIČALIJAMA NA RADU, GRANIČNIM VRIJEDNOSTIMA IZLOŽENOSTI I BIOLOŠKIM GRANIČNIM VRIJEDNOSTIMA	
ITA	Italia	Decreto Legislativo 9 Aprile 2008, n.81	
NLD	Nederland	Regeling van de Minister van Sociale Zaken en Werkgelegenheid van 13 mei2024, nr. 2024-0000092805, tot wijziging van deArbeidsomstandighedenregeling in verband met de implementatie vanRichtlijn 2022/431	
POL	Polska	ROZPORZĄDZENIE MINISTRA RODZINY, PRACY I POLITYKI SPOŁECZNEJ z dnia 24 czerwca 2024 r. zmieniające rozporządzenie w sprawie najwyższych dopuszczalnych stężeń i natężeń czynników szkodliwych dla zdrowia w środowisku pracy	
ROU	România	HOTĂRÂRE nr. 179 din 28 februarie 2024 pentru modificarea și completarea Hotărârii Guvernului nr. 1.093/2006 privind stabilirea cerințelor minime de securitate și sănătate pentru protecția lucrătorilor împotriva riscurilor legate de expunerea la agenți ca	
SVN	Slovenija	Pravilnik o varovanju delavcev pred tveganji zaradi izpostavljenosti rakotvornim, mutagenim ali reprotoksičnim snovem pri delu. Ljubljana, četrtek 4. 4. 2024	
GBR	United Kingdom	EH40/2005 Workplace exposure limits (Fourth Edition 2020)	
EU	OEL EU	Directive (EU) 2022/431; Directive (EU) 2019/1831; Directive (EU) 2019/130; Directive (EU) 2019/983; Directive (EU) 2017/2398; Directive (EU) 2017/164; Directive 2009/161/EU; Directive 2006/15/EC; Directive 2004/37/EC; Directive 2000/39/EC; Directive 98/24/EC; Directive 91/322/EEC.	
	ACGIH	ACGIH 2025	

EPY 12.1.0 - SDS 1004.1

SECTION 8. Exposure controls/personal protection ... / >>

2-(2-BUTOXYETHOXY)ETHANOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ALB	67,5	10	101,2	15	
AGW	DEU	67	10	100,5	15	Hinweis, 11
MAK	DEU	67	10	100,5	15	Hinweis
VLA	ESP	67,5	10	101,2	15	
VLEP	FRA	67,5	10	101,2	15	
GVI/KGVI	HRV	67,5	10	101,2	15	
VLEP	ITA	67,5	10	101,2	15	
TGG	NLD	50		100		SKIN
NDS/NDSch	POL	67		100		
TLV	ROU	67,5	10	101,2	15	
MV	SVN	67,5	10	101,2	15	
WEL	GBR	67,5	10	101,2	15	
OEL	EU	67,5	10	101,2	15	
ACGIH		66	10			INHAL

Predicted no-effect concentration - PNEC

Normal value in fresh water	1,1	mg/l
Normal value in marine water	0,11	mg/l
Normal value for fresh water sediment	4,4	mg/kg
Normal value for marine water sediment	0,44	mg/kg
Normal value for marine water, intermittent release	11	mg/l
Normal value of STP microorganisms	200	mg/l
Normal value for the food chain (secondary poisoning)	0,056	g/kg
Normal value for the terrestrial compartment	0,32	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				5 mg/kg				
Inhalation	60,7 mg/m3	40,5 mg/m3		40,5 mg/m3	101,2 mg/m3		67,5 mg/m3	67,5 mg/m3
Skin				50 mg/kg		83 mg/kg		

2-OCTYL-2H-ISOTHIAZOL-3-ONE

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
AGW	DEU	0,05		0,1		INHAL
AGW	DEU	0,05		0,1		SKIN
MAK	DEU	0,05		0,1		INHAL
MAK	DEU	0,05		0,1		SKIN
MV	SVN	0,05		0,1		INHAL
MV	SVN	0,05		0,1		SKIN

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,0022	mg/l
Normal value in marine water	0,00022	mg/l
Normal value for fresh water sediment	0,0475	mg/kg
Normal value for marine water sediment	0,00475	mg/kg
Normal value for water, intermittent release	0,00122	mg/l
Normal value for the terrestrial compartment	0,0082	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Oral				0,167 mg/kg				
Inhalation				0,29 mg/m3				1,63 mg/m3
Skin				0,0134 mg/kg				

VOLTECO S.P.A

ER05 - CP0

Revision nr.2
Dated 10/04/2026
Printed on 10/04/2026
Page n. 6 / 15
Replaced revision:1 (Dated 03/09/2025)

EN

SECTION 8. Exposure controls/personal protection ... / >>

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE

(3:1)

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
MAK	DEU	0,2		0,4		INHAL
NDS/NDSch	POL	0,2		0,4		SKIN

ETHYLENE GLYCOL

Threshold Limit Value

Type	Country	TWA/8h		STEL/15min		Remarks / Observations
		mg/m3	ppm	mg/m3	ppm	
TLV	ALB	52	20	104	40	SKIN
AGW	DEU	26	10	52	20	SKIN 11
MAK	DEU	26	10	52	20	SKIN
VLA	ESP	52	20	104	40	SKIN
VLEP	FRA	52	20	104	40	SKIN
GVI/KGVI	HRV	52	20	104	40	SKIN
VLEP	ITA	52	20	104	40	SKIN
TGG	NLD	52		104		SKIN damp
NDS/NDSch	POL	15		50		SKIN
TLV	ROU	52	20	104	40	SKIN
MV	SVN	52	20	104	40	SKIN
WEL	GBR	52	20	104	40	SKIN
OEL	EU	52	20	104	40	SKIN
ACGIH			25		50	
ACGIH				10		INHAL

Predicted no-effect concentration - PNEC

Normal value in fresh water	10	mg/l
Normal value in marine water	1	mg/l
Normal value for fresh water sediment	37	mg/kg
Normal value for marine water sediment	3,7	mg/kg
Normal value for water, intermittent release	10	mg/l
Normal value of STP microorganisms	199,5	mg/l
Normal value for the terrestrial compartment	1,53	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation			7 mg/m3				35 mg/m3	
Skin			53	53 mg/kg			35	106 mg/kg

Diuron

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00032	mg/l
Normal value in marine water	0,000032	mg/l
Normal value for fresh water sediment	0,052	mg/kg
Normal value for marine water sediment	0,005	mg/kg
Normal value for water, intermittent release	0,00022	mg/l
Normal value of STP microorganisms	58	mg/l
Normal value for the terrestrial compartment	0,012	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local	Acute systemic	Chronic local	Chronic systemic
Inhalation								0,17 mg/m3
Skin								5,79 mg/kg

SECTION 8. Exposure controls/personal protection ... / >>

Zinc pyrithione

Predicted no-effect concentration - PNEC

Normal value in fresh water	0,00009	mg/l
Normal value in marine water	0,00009	mg/l
Normal value for fresh water sediment	0,009	mg/kg
Normal value for marine water sediment	0,009	mg/kg
Normal value of STP microorganisms	0,01	mg/l
Normal value for the terrestrial compartment	1,02	mg/kg

Health - Derived no-effect level - DNEL / DMEL

Route of exposure	Effects on consumers				Effects on workers			
	Acute local	Acute systemic	Chronic local	Chronic systemic	Acute local systemic	Acute systemic	Chronic local	Chronic systemic
Skin								0,01 mg/kg

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

HAND PROTECTION

Protect hands with category III work gloves.

The following should be considered when choosing work glove material (see standard EN 374): compatibility, degradation, permeability time. The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN ISO 16321).

RESPIRATORY PROTECTION

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. Use a mask with a type B filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387).

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

Product residues must not be indiscriminately disposed of with waste water or by dumping in waterways.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Information
Appearance	dense liquid	
Colour	as showed in color folder	
Odour	characteristic	
Odour threshold	not applicable	
Melting point / freezing point	not available	
Initial boiling point	103 °C	
Flammability	not available	
Lower explosive limit	not applicable	
Upper explosive limit	not applicable	
Flash point	> 60 °C	
Auto-ignition temperature	204 °C	
Decomposition temperature	not applicable	
pH	8	
Kinematic viscosity	not applicable	
Dynamic viscosity	not applicable	
Solubility	not applicable	
Partition coefficient: n-octanol/water		

SECTION 9. Physical and chemical properties ... / >>

Vapour pressure	not applicable	
Density and/or relative density	2310	Pa
Relative vapour density	1,983	Temperature: 20 °C
Particle characteristics	not available	Temperature: 20 °C
	not applicable	

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Information not available

9.2.2. Other safety characteristics

COV Directive 2010/75/EU	0% peso
Density of C.O.V. at 20 °C	0 kg/m ³ (0 g/L)
Medium carbon number	4
Average molecular weight	115,15 g/mol
VOC (directive 2004/42/EC)	17,85 kg/m ³ (17,85 g/L) 20°C (Cat. A.C): 40 g/L (2010)

SECTION 10. Stability and reactivity**10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

ETHYLENE GLYCOL

In the air absorbs moisture. Decomposes at temperatures above 200°C/392°F.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

2-(2-BUTOXYETHOXY)ETHANOL

May react with: oxidising substances. May form peroxides with: oxygen. Develops hydrogen on contact with: aluminium. May form explosive mixtures with: air.

ETHYLENE GLYCOL

Risk of explosion on contact with: perchloric acid. May react dangerously with: chlorosulphuric acid, sodium hydroxide, sulphuric acid, phosphorus pentasulphide, chromium (III) oxide, chromyl chloride, potassium perchlorate, potassium dichromate, sodium peroxide, aluminium. Forms explosive mixtures with: air.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

2-(2-BUTOXYETHOXY)ETHANOL

Avoid exposure to: air.

ETHYLENE GLYCOL

Avoid exposure to: sources of heat, naked flames.

10.5. Incompatible materials**2-(2-BUTOXYETHOXY)ETHANOL**

Incompatible with: oxidising substances, strong acids, alkaline metals.

10.6. Hazardous decomposition products**2-(2-BUTOXYETHOXY)ETHANOL**

May develop: hydrogen.

ETHYLENE GLYCOL

May develop: hydroxyacetaldehyde, glyoxal, acetaldehyde, methane, carbon monoxide, hydrogen.

SECTION 11. Toxicological information

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.
It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

ETHYLENE GLYCOL

WORKERS: inhalation; contact with the skin.

POPULATION: inhalation of ambient air; contact with the skin of products containing the substance.

2-(2-BUTOXYETHOXY)ETHANOL

WORKERS: inhalation; contact with the skin.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

ETHYLENE GLYCOL

Ingestion initially stimulates the central nervous system; later replaced by a phase of depression. There may be kidney damage, with anuria and uremia. Over-exposure symptoms are: vomiting, drowsiness, difficulty in breathing, convulsions. The lethal dose for humans is approx. 1.4 ml/kg.

2-(2-BUTOXYETHOXY)ETHANOL

May be absorbed by inhalation, ingestion and skin contact; is irritating for the skin and especially for the eyes. May cause damage to the spleen. At room temperature the danger of inhalation is unlikely, due to the low vapour pressure of the substance.

Interactive effects

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

Not classified (no significant component)

ATE (Oral) of the mixture:

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

ETHYLENE GLYCOL

LD50 (Dermal):

> 3500 mg/kg Rabbit

LD50 (Oral):

500 mg/kg

2-(2-BUTOXYETHOXY)ETHANOL

LD50 (Dermal):

2700 mg/kg Rabbit

LD50 (Oral):

3384 mg/kg Rat

1,2-benzisothiazolin-3-one

LD50 (Oral):

450 mg/kg/bw

LC50 (Inhalation mists/powders):

0,21 mg/l

Diuron

LD50 (Oral):

4150 mg/kg Rat

Zinc pyrithione

LD50 (Oral):

300 mg/kg Rat

LC50 (Inhalation mists/powders):

0,14 mg/l Rat

2-OCTYL-2H-ISOTHIAZOL-3-ONE

LD50 (Dermal):

311 mg/kg

LD50 (Oral):

125 mg/kg Rat

LC50 (Inhalation mists/powders):

0,5 mg/l

SECTION 11. Toxicological information ... / >>

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

LD50 (Dermal): > 50 mg/kg Rabbit

LD50 (Oral): > 50 mg/kg Rat

LC50 (Inhalation mists/powders): 0,31 mg/l/4h Rat

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

May produce an allergic reaction.

Contains:

REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)

2-OCTYL-2H-ISOTHIAZOL-3-ONE

1,2-benzisothiazolin-3-one

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

ETHYLENE GLYCOL

Available studies have shown no carcinogenic potential. In a carcinogenicity study lasting two years, carried out by the US National Toxicology Program (NTP), in which ethylene glycol was administered in the feed, "no evidence of carcinogenic activity" in male and female B6C3F1 mice was observed (NTP, 1993).

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

This product is dangerous for the environment and the aquatic organisms. In the long term, it has negative effects on the aquatic environment.

12.1. Toxicity

ETHYLENE GLYCOL

LC50 - for Fish

EC50 - for Crustacea

EC50 - for Algae / Aquatic Plants

53000 mg/l/96h Pimephales promelas

51000 mg/l/48h Daphnia magna

24000 mg/l/168h Selenastrum capricornutum

2-(2-BUTOXYETHOXY)ETHANOL

LC50 - for Fish

EC50 - for Crustacea

1300 mg/l/96h Pimephales promelas

2850 mg/l/24h Daphnia magna

ER05 - CP0

SECTION 12. Ecological information ... / >>

EC50 - for Algae / Aquatic Plants	53 mg/l/192h <i>Microcystis aeruginosa</i>
1,2-benzisothiazolin-3-one	
LC50 - for Fish	> 2,15 mg/l/96h
EC50 - for Crustacea	> 2,9 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 70 µg/L/72h
Chronic NOEC for Algae / Aquatic Plants	> 40,3 µg/L
Diuron	
LC50 - for Fish	14,7 mg/l/96h <i>Oncorhynchus mykiss</i>
EC50 - for Crustacea	1,4 mg/l/48h <i>Daphnia magna</i>
EC50 - for Algae / Aquatic Plants	0,022 mg/l/96h <i>Desmodesmus subspicatus</i>
Chronic NOEC for Fish	> 0,001 mg/l
Chronic NOEC for Crustacea	> 0,001 mg/l
Zinc pyrithione	
LC50 - for Fish	0,003 mg/l/96h <i>Pimephales promelas</i>
EC50 - for Crustacea	0,008 mg/l/48h <i>Daphnia magna</i>
Chronic NOEC for Crustacea	0,022 mg/l <i>Daphnia magna</i>
2-OCTYL-2H-ISOTHIAZOL-3-ONE	
LC50 - for Fish	> 0,001 mg/l/96h
EC50 - for Crustacea	> 0,001 mg/l/48h
EC50 - for Algae / Aquatic Plants	> 0,001 mg/l/72h
Chronic NOEC for Fish	> 0,001 mg/l
Chronic NOEC for Crustacea	> 0,001 mg/l

12.2. Persistence and degradability

ETHYLENE GLYCOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	90% - 14d
2-(2-BUTOXYETHOXY)ETHANOL	
Solubility in water	1000 - 10000 mg/l
Rapidly degradable	
1,2-benzisothiazolin-3-one	
Solubility in water	1,288 g/l
2-OCTYL-2H-ISOTHIAZOL-3-ONE	
Solubility in water	500 mg/l
REACTION MASS OF 5-CHLORO-2- METHYL-2H-ISOTHIAZOL-3-ONE AND 2-METHYL-2H-ISOTHIAZOL-3-ONE (3:1)	
NOT rapidly degradable	

12.3. Bioaccumulative potential

ETHYLENE GLYCOL	
Partition coefficient: n-octanol/water	-1,36
BCF	10
2-(2-BUTOXYETHOXY)ETHANOL	
Partition coefficient: n-octanol/water	0,56
BCF	0,46
1,2-benzisothiazolin-3-one	
Partition coefficient: n-octanol/water	0,7
Diuron	
BCF	57

12.4. Mobility in soil

SECTION 12. Ecological information ... / >>

ETHYLENE GLYCOL	
Partition coefficient: soil/water	0
2-(2-BUTOXYETHOXY)ETHANOL	
Partition coefficient: soil/water	48
1,2-benzisothiazolin-3-one	
Partition coefficient: soil/water	9,33

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage $\geq$ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations**13.1. Waste treatment methods**

Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

The management of waste arising from the use or dispersal of this product must be organised in accordance with occupational safety regulations. See section 8 for possible need for PPE.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

SECTION 14. Transport information

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

14.1. UN number or ID number

not applicable

14.2. UN proper shipping name

not applicable

14.3. Transport hazard class(es)

not applicable

14.4. Packing group

not applicable

14.5. Environmental hazards

not applicable

14.6. Special precautions for user

not applicable

SECTION 14. Transport information ... / >>**14.7. Maritime transport in bulk according to IMO instruments**

Information not relevant

SECTION 15. Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**Seveso Category - Directive 2012/18/EU:

None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors
not applicableSubstances in Candidate List (Art. 59 REACH)On the basis of available data, the product does not contain any SVHC in percentage $\geq$ than 0,1%.Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Information not available

15.2. Chemical safety assessment

A chemical safety assessment has not been performed for the preparation/for the substances indicated in section 3.

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Carc. 1B	Carcinogenicity, category 1B
Repr. 1B	Reproductive toxicity, category 1B
Acute Tox. 2	Acute toxicity, category 2
Acute Tox. 3	Acute toxicity, category 3
Acute Tox. 4	Acute toxicity, category 4
STOT RE 1	Specific target organ toxicity - repeated exposure, category 1
STOT RE 2	Specific target organ toxicity - repeated exposure, category 2
Skin Corr. 1B	Skin corrosion, category 1B
Skin Corr. 1C	Skin corrosion, category 1C
Skin Corr. 1	Skin corrosion, category 1
Eye Dam. 1	Serious eye damage, category 1
Eye Irrit. 2	Eye irritation, category 2
Skin Irrit. 2	Skin irritation, category 2
Skin Sens. 1A	Skin sensitization, category 1A
Aquatic Acute 1	Hazardous to the aquatic environment, acute toxicity, category 1
Aquatic Chronic 1	Hazardous to the aquatic environment, chronic toxicity, category 1
Aquatic Chronic 3	Hazardous to the aquatic environment, chronic toxicity, category 3
H350	May cause cancer.
H360D	May damage the unborn child.
H310	Fatal in contact with skin.

SECTION 16. Other information ... / >>

H330	Fatal if inhaled.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H302	Harmful if swallowed.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.
EUH071	Corrosive to the respiratory tract.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent, bioaccumulative and toxic
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PMT: Persistent, mobile and toxic
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very persistent and very bioaccumulative
- vPvM: Very persistent and very mobile
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
10. Regulation (EU) 2015/1221 (VII Atp. CLP) of the European Parliament
11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
12. Regulation (EU) 2016/1179 (IX Atp. CLP)
13. Regulation (EU) 2017/776 (X Atp. CLP)
14. Regulation (EU) 2018/669 (XI Atp. CLP)
15. Regulation (EU) 2019/521 (XII Atp. CLP)
16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
17. Regulation (EU) 2019/1148
18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)

ER05 - CP0

SECTION 16. Other information ... / >>

19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
23. Delegated Regulation (UE) 2023/707
24. Delegated Regulation (UE) 2023/1434 (XIX Atp. CLP)
25. Delegated Regulation (UE) 2023/1435 (XX Atp. CLP)
26. Delegated Regulation (UE) 2024/197 (XXI Atp. CLP)
27. Delegated Regulation (UE) 2024/2564 (XXII Atp. CLP)
28. Regulation (EU) 2024/2865

- The Merck Index. - 10th Edition
- Handling Chemical Safety
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.

Changes to previous review:

The following sections were modified:

02 / 03 / 05 / 08 / 09 / 10 / 11 / 12 / 15 / 16.